MOEN

Buy it for looks. Buy it for life.®

- DESCRIPTION
 Reflex[™] pulldown system offers smooth operation, easy movement and secure docking
- Metal construction with various finishes identified by suffix
- Duralock® quick connect installation
- PowerClean Spray
- Flexible supply lines with 3/8"CC fittings connect directly to supply stop
- High arc spout provides height and reach to fill or clean large
- pots while pull out wand provides the maneuverability for cleaning or rinsing 360° rotating spout

OPERATION

- Lever style handle
- Temperature controlled by 100° arc of handle travel
- Operates with less than 5 lbs. of force
- Operates in stream or spray mode in the pulldown or retracted position


FLOW

- Flow is limited to 1.5 gpm (5.7 L/min) at 60 psi
- CARTRIDGE
- 1255[™] Duralast[™] cartridge for Single-Handle Faucets **STANDARDS**
- Third party certified to IAPMO Green, ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein including NSF 61/9 & 372
- Meets CalGreen and Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- The backflow protection system in the device consists of two inde pendently operating check valves, a primary and a secondary which prevent backflow
- ADA for lever handle

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations





Edwyn[™] Single Handle **Pulldown Kitchen Faucet** Model: 87028 series

NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THRU 1, 2, 3 and 4 HOLE, 1-1/2" (38mm) MIN. DIA.

(1 HOLE FOR SOAP DISPENSER)

