ΜΟΕΝ

Buy it for looks. Buy it for life.®

FAUCET DESCRIPTION

- Reflex^m pulldown system offers smooth operation, easy movement and secure docking
- Power Clean™ spray technology Metal construction with various finishes identified by suffix
- Duralock[™] quick connect system Power Boost[™] Technology provides boosted water performance with the push of a button
- Flexible supply lines with 3/8" compression fittings High arc spout provides height and reach to fill or clean large pots while pull out wand provides the maneuverability for cleaning or rinsing 360° rotating spout

OPERATION

- Lever style handle
- Temperature controlled by 100° arc of handle travel
- Operates with less than 5 lbs. of force
- Operates in stream or spray mode in the pullout or retracted position
- When filling a vessel outside the sink, the pause feature conveniently stops the flow of water as the wand passes over the counter top

FLOW

- Standard flow is limited to 1.5 gpm (5.7 L/min) at 60 psi
- Power Boost[™] Button activates Boosted Stream and Boosted Spray

CARTRIDGE


1255[™] Duralast[™] cartridge for Single-Handle Faucets

STANDARDS

- Third party certified to IAPMO Green, ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein
- Certified to NSF 61/9 & 372
- Meets CalGreen and Georgia SB370 requirements Complies with California Proposition 65 and with the Federal Safe Drinking
- Water Act The backflow protection system in the device consists of two
- independently operating check valves, a primary and a secondary which prevent backflow
- ADA (5) for lever handle

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- 10 year limited warranty when used in a multifamily installation
- 5 year limited warranty when used in a commercial installation
- Visit www.moen.com/support for complete details and limitations



HADLEY[™] **Single Handle High Arc Pulldown Kitchen Faucet**

Models: 87245 series

NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THROUGH 1 OR 3 HOLES, 1-1/2" (38mm) MIN. DIA.



