

Broan brings you Spire, an exciting new shape in a pro-style hood. The new design incorporates modern features like the quiet Captur™ system and LED lighting.

SIZE	STAINLESS	GREASE FILTER(S) (replacement)	NON-DUCTED FILTER(S)
30-in.	BPDP130SS	HPFA424 (Type "B5")	HPF24 (Type "Xb")
36-in.	BPDP136SS	HPFA430 (Type "C5")	HPF30 (Type "Xc")
42-in.	BPDP142SS	HPFA436 (Type "D5")	HPF36 (Type "Xd")
48-in.	BPDP148SS	HPFA442 (Type "E5")	HPF42 (Type "Xe")

PERFORMANCE									
Don't Orientation	Size	Damper	Sones		CFM @ 0.1 Ps				
Duct Orientation			Normal	High	Normal	High			
Vertical - Rectangular	3¼-in. x 10-in.	Included	0.3	6.5	120	360			
Horizontal - Rectangular	3¼-in. x 10-in.	Included	0.3	6.5	120	400			
Round - Vertical	7-in.	Sold Separately	0.5	6.5	120	370			

FEATURES					
Control type	2-speed Deluxe Rocker				
Delay off	no				
Filter Clean Reminder	no				
Heat Sentry™	no				
ADA Capable	yes				
Lighting	1-level LED (included)				
Grease Filter(s)	Hybrid Baffle (Qty. 2)				
Installation Hardware	EZ1 brackets				
ENERGY STAR®	no				
Recirculation	Non-ducted filter(s) sold separately				

AC INPUT

120V, 60 Hz - 1.4 AMPS

OPTIONAL ACCESSORIES

7-in. Round Damper BP87

MOUNTING HEIGHT

18-in. to 24-in. from cooktop to bottom of hood

LIMITED WARRANTY

1-year


BPDP1 SERIES

SPECIFICATION SHEET


3-year (LED modules only)

(See installation manual for full warranty text.)

FOR INDOOR USE ONLY











HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in AMCA's state-ofthe-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.