



Decorator Combination Devices

Space-saving architectural combination devices add elegance and style.

COOPER Wiring Devices



Decorator Combination Devices



High style solutions

Cooper Wiring Devices' Decorator Combination switches add elegance to residential and light commercial applications. Decorator design features easy, smooth actuation of the rocker panels.

Switch Combinations


FEATURES

- 120/277V/AC rating is ideal for incandescent or fluorescent lighting fixtures.
- Thermoplastic rocker, top and backbody are virtually unbreakable to deliver years of durable performance.
- Ultrasonic welding and integrated construction of the strap and body provide superior ground integrity even under heavy use.
- Durable, injection molded housings and PVC resin comply with UL94 V0 flammability ratings.
- Automatic grounding system eliminates the need for bonding jumper in grounded metal enclosure and provides redundant measure of ground continuity where a jumper is used.
- Steel mounting strap is zinc-plated for added corrosion resistance.
- Convenient patented built-in wire stripper speeds installation.
- Backwire clamps on side terminals provide for easy installation of #12 and #14 wire.
- Terminal screws are backed out and ready for wiring to enhance ease of installation.
- Break-off provision on switches for wiring both devices on the same circuit or on separate circuits.
- Triple wipe blade contacts and double wipe ground contacts to insure long-term plug retention (7730).
- Tri-combo screw heads offer greater installation flexibility.


Decorator Commercial Specification Grade




Rating	Description	Catalog No.	Available Colors
15 A V	120/277V/AC Two Single-Pole Switches	□ 7728__	A, BK, LA, V, W
	Three Single-Pole Switches	□ 7729__	A, BK, LA, V, W
	Single-Pole Switch with NEMA NEMA 5-15 15A 125V Receptacle	□ 7730__	A, BK, LA, V, W
	Two 3-Way Switches	□ 7731__	A, BK, LA, V, W
	One Single-Pole Switch with One 3-Way Switch	□ 7732__	A, BK, LA, V, W



7728



7729



7730

Related Products

Architectural Mid-Size Screwless Wallplates



Description	Overall Size	Catalog No.	Available Colors
1-Gang Decorator	4.88" (123.8mm) H x 3.13" (79.4mm) W	□ PJS26__	A, B, BK, GY, LA, V, W
2-Gang Decorator	4.88" (123.8mm) H x 4.94" (125.4mm) W	□ PJS262__	A, B, BK, GY, LA, V, W
3-Gang Decorator	4.88" (123.8mm) H x 6.75" (171.5mm) W	□ PJS263__	A, BK, LA, V, W
4-Gang Decorator	4.88" (123.8mm) H x 8.62" (217.5mm) W	□ PJS264__	A, BK, LA, V, W
5-Gang Decorator	4.88" (123.8mm) H x 11.38" (288.9mm) W	□ PJS265__	A, BK, LA, V, W
6-Gang Decorator	4.88" (123.8mm) H x 12.19" (309.6mm) W	□ PJS266__	A, BK, LA, V, W

For ordering, include Cat. No. followed by the color code: A (Almond), B (Brown), BK (Black), GY (Gray), LA (Light Almond), V (Ivory), W (White).


TESTING & CODE COMPLIANCE

- cULus Listed to UL20/UL498, file no. E18704 (combination).
- cULus Listed to UL 514D, file no. E33216 (wallplates).
- Horsepower rated for motor loads per UL 20: 15A switch, 1/2 hp @120V/AC, 2 hp @240V/AC, max. 12A.

MATERIAL CHARACTERISTICS

- PVC (combination); Polycarbonate (wallplates)
- Environmental: Flammability meets UL 94 requirements; combination V0 rated; wallplates V2 rated.
- Temperature Rating: combination: -20°C to 60°C (-4°F to 140°F); wallplates -40°C to 65°C (-40°F to 149°F).

Cooper Wiring Devices is a valuable trademark of Cooper Industries in the U.S. and other countries. You are not permitted to use the Cooper Trademarks without the prior written consent of Cooper Industries. ©2008 Cooper Industries, Ltd.



Screwless Wallplates

Cooper Wiring Devices

United States
203 Cooper Circle
Peachtree City, GA 30269
P: 866-853-4293 F: 800-329-3055

Canada
5925 McLaughlin Road
Mississauga, Ontario, L5R 1B8
P: 800-267-1042 F: 800-761-5748

Mexico
Industrias Royer, S.A. de C.V.
Tres Anegas #404
Col. Nueva Industrial Vallejo
C.P. 07700, Mexico D.F.
P: 5747-6228 | 5747-6229
F: 5752-5336

www.cooperwiringdevices.com