

**CHAMPION® 4 ELONGATED RIGHT HEIGHT™  
ONE-PIECE TOILET**

**2034.014**

- Vitreous china
- EverClean™ anti-microbial surface which inhibits the growth of stain and odor causing bacteria, mold, and mildew
- Low-consumption (6.0 Lpf/1.6 gpf)
- Features **Champion® 4 Flushing System** performance platform
- 4" non-adjustable, piston action Accelerator™ flush valve
- 16-1/2" rim height for accessible applications
- Elongated siphon action jetted bowl
- 2-3/8" fully-glazed trapway
- Chrome trip lever
- 100% factory flush tested
- 2 bolt caps
- 10 year warranty



**Nominal Dimensions:**


756 x 451 x 749mm  
(29-3/4" x 17-3/4" x 29-1/2")

Fixture only, seat and supply by others

**Compliance Certifications -**

**Meets or Exceeds the Following Specifications:**

- ASME A112.19.2M for Vitreous China Fixtures - includes Flush Performance, Ball Pass Diameter, Trap Seal Depth and all Dimensions



**To Be Specified:**

- Color:
  - White  Bone  Silver  Linen  Black
- Seat:
  - Champion® Slow Close Elongated #5325.010
  - Rise & Shine Elongated #5324.019
- Supply with Stop (by other):

**NOTES:**

THIS TOILET IS DESIGNED TO ROUGH-IN AT A MINIMUM DIMENSION OF 305MM (12") FROM FINISHED WALL TO C/L OF OUTLET. SUPPLY NOT INCLUDED WITH FIXTURE AND MUST BE ORDERED SEPARATELY.  
\* DIMENSION SHOWN FOR LOCATION OF SUPPLY IS SUGGESTED.

**IMPORTANT:** Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI Standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

**MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE BUILDING FACILITIES-CHECK LOCAL CODES.**

- When installed, top of seat meets minimum requirement of 432 to 483mm (17" to 19") from the finished floor.

**CHAMPION® 4**  
Flushing System