

SOHO_®

Features

- Vitreous china
- Wall-mount
- Single center hole
- With overflow
- Drilled for concealed arm carrier
- Optional soap dispenser hole on left (-L) or right (-R)
- 20" (50.8 cm) x 18" (45.7 cm)


Codes/Standards Applicable

Specified model meets or exceeds the following:

- ADA
- ICC/ANSI A117.1
- CSA B651
- OBC
- ASME A112.19.2/CSA B45.1

WALL-MOUNT LAVATORY K-2084

ADA CSA B651 OBC



Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Accessories

- CP: Polished Chrome
- Other: Refer to Price Book for additional colors/finishes

Specified Model

Model	Description	Colors/Finishes	
K-2084	Single-hole lavatory less soap dispenser hole	□ 0	☐ Other
K-2084-L	Single-hole lavatory with soap dispenser hole on left	□ 0	☐ Other
K-2084-R	Single-hole lavatory with soap dispenser hole on right	□ 0	☐ Other
K-2084-N	Single-hole lavatory less overflow	□ 0	☐ Other
K-2084-NL	Single-hole lavatory with soap dispenser hole on left less overflow	□ 0	□ Other
K-2084-NR	Single-hole lavatory with soap dispenser hole on right less overflow	0	☐ Other

Recommended Accessories				
K-8998	Trap	□ CP	☐ Other	

Product Specification

The wall-mount lavatory shall be made of vitreous china. Lavatory shall be 20" (50.8 cm) in length, and 18" (45.7 cm) in width. Lavatory shall have single-hole drilling. Lavatory shall have overflow. Lavatory shall be drilled for concealed arm carrier. Lavatory shall have optional soap dispenser hole on left (-L) or right (-R). Lavatory shall be Kohler Model K-2084-____.

SOHO_®

Technical Information

Fixture*:				
Basin area	18" (45.7 cm) x 13" (33 cm)			
Water depth	4-7/8" (12.4 cm)			
Drain hole	1-3/4" (4.4 cm) D.			
* Approximate measurements for comparison only.				

Spout hole	1-3/8" (3.5 cm) D.
Soap dispenser hole	1-1/4" (3.2 cm) D.

Installation Notes

Install this product according to the installation guide.

Will comply with **ADA** when installed per Section 606 Lavatories of the Act.

Will comply with **CSA B651** when installed per Clause 4.3.3 of the standard.

Will comply with **OBC** when installed per Clause 3.8.3.11.

