LG DISHWASHERS

LDT8786_

Top Control Dishwasher

15 Place Settings

TrueSteam® Technology

QuadWash™

10 Wash Cycles

EasyRack™ Plus with Fully Adjustable Color-coded Tines

44 dBA LoDecibel™ Quiet Operation

NeveRust™ Stainless Steel Tub

ENERGY STAR® Qualified

Available in Black Stainless Steel and Stainless Steel

CAPACITY	
Total Place Settings	15
Upper Rack Dish Height Limit	7.1"
Lower Rack Dish Height Limit	12.5"
RACKS AND BASKETS	
Cutlery Baskets	•
Cup Rack	•
Stemware Holders	•
Fold Down Tines	• (Full Fold on Upper & Lower)
BPA-Free Nylon Coated Racks and Tines	•
Rack Handle	• (Upper/Lower)
Glide Rail	•
Height Adjustability	• Easy One Touch (3 Level)
EasyRack™ Plus System	•
Upper Rack Color-Coded Foldable Tines	•
Lower Rack Color-Coded Foldable Tines	•
Height Adjustable Upper Rack	•
Height Adjustable 3rd Rack	•
STYLE AND DESIGN	
Electronic Controls	Touch
SignaLight™ Cycle Indicator Lights	3
Tub Material	NeveRust™ Stainless Steel
Tub Insulation	Damping Sheet, Sound Absorbing Material (felt), Base
Handle	Matching Commercial Handle
Available Colors	Black Stainless Steel, Stainless Steel
FEATURES	
LoDecibel™ Quiet Operation	44 dBA
Slim Direct Drive Motor	•
Overflow Detector	•
120°F Inlet Water Capability	•
3-Stage Filtration System	•
SenseClean™ Wash System	•
Vario Wash	•
Variable Spray Intensities	•
No. of Spray Arms	3 (Top, Upper, Lower)
Multi-Level Water Direction	**
Hybrid Condensing Drying System	



	Stainless steel model shown
Detergent and Rinse-Aid Dispenser	•
Rinse-Aid Indicator	•
Hidden Water Heater	•
Safety Float Switch (Leaks)	•
Soil (Turbidity) Sensor	•
Status Indicator	•
End of Cycle Indicator	Beeper + END Indication on Display
PERFORMANCE	
Number of Wash Cycles	 (Auto, Heavy, Delicate, Refresh, Normal, Turbo, Download Cycle, Machine Clean, Rinse, Express)
Number of Wash Options	9 (Dual Zone, Half Load, Energy Saver, Pre-Steam, High Temp, Extra Dry, Delay Start (up to 12 hrs), Control Locl Night Dry)
TrueSteam™	•
QuadWash™	•
ENERGY / WATER	
Water Factor (WF)	2.8
Energy Use (kWh/Year)	258 kWh/Year
ENERGY STAR® Qualified	•
CEE Tier	1
DIMENSIONS	
Unit Dimensions (WxHxD)	23.75" x 33.6" x 24.6"
Depth with Door Closed (Handle)	27 1/8"
Depth with Door Open	50.5"
Carton Dimensions (WxHxD)	28" x 34.7" x 29.6"
Clearances (WxHxD)	24" x 33.5" x 24"
Weight (Unit / Carton)	81.6 lbs / 94.8 lbs
Container Stuffing Quantity	20 ft Normal: 42 unit 40 ft Normal: 96 unit 40 ft High Cubic: 140 unit
LIMITED WARRANTY	
Limited Warranty	1 Year Labor & Parts, 5 Years Control Board/Rack, 10 Year Motor, Lifetime on Stainless Steel Door Liner or Tu
UPC CODES	
LDT8786ST Stainless Steel	048231016339
LDT8786BD Black Stainless Steel	048231017329