



## Specifications – Thermostat® OSB Radiant Barrier

**Thermostat® oriented strand board (OSB) radiant barrier sheathing** is designed for roof sheathing applications, reflecting up to 97% of the sun’s radiant heat and keeping it from being absorbed into the attic of your home. That means you can maintain indoor comfort while potentially lowering cooling energy consumption.

Backed with a specially designed aluminum foil/craft paper laminate, this high-quality Georgia-Pacific OSB sheathing is installed foil side down facing into the attic space. Since aluminum foil is highly reflective, up to 97% of the radiant heat is reflected from entering the attic space.

### Available Sizes

**Square Edge**                      3’-11<sup>7</sup>/<sub>8</sub>” (1.216 m) x 7’-11<sup>7</sup>/<sub>8</sub>” (2.435 m) – sized for 4’ x 8’  
    3’-11<sup>7</sup>/<sub>8</sub>” (1.216 m) x 8’-11<sup>7</sup>/<sub>8</sub>” (2.740 m) – sized for 4’ x 9’  
    3’-11<sup>7</sup>/<sub>8</sub>” (1.216 m) x 9’-11<sup>7</sup>/<sub>8</sub>” (3.044 m) – sized for 4’ x 10’

### Building Code Performance Categories, Panel Thickness

- 7/16 CAT, 0.418” (10.61 mm)
- 15/32 CAT, 0.451” (11.45 mm)
- 19/32 CAT, 0.578” (14.68 mm)

### Specifications

<b>Thickness Tolerance</b>	± <sup>1</sup> / <sub>32</sub> ” (± 0.79)
<b>Length/Width Tolerance</b>	+0, - <sup>1</sup> / <sub>8</sub> ” (+0, -3.2 mm)
<b>Straightness Tolerance</b>	± <sup>1</sup> / <sub>16</sub> ” (±1.6 mm)
<b>Squareness Tolerance</b>	± <sup>1</sup> / <sub>8</sub> ” (±3.2 mm)
<b>Classification</b>	<b>Exposure 1</b> – OSB suitable for uses not permanently exposed to the weather. Panels classified as Exposure 1 are intended to resist the effects of moisture on structural performance as may occur due to construction delays, or other conditions of similar severity.
<b>Code Fire Classification</b>	Class III or C
<b>Flame Spread Rating</b>	75-200, smoke-developed index <450
<b>Building Code Compliance</b>	PS 2-04
<b>Foil</b>	Foil utilizes a Kraft backer and bright (polished) aluminum foil with emissivity of .03.

### Other Information

<b>Forestry Certification</b>	Thermostat OSB panels are made from Sustainable Forestry Initiative® (SFI®) certified responsible wood sources.
<b>NGBS Green Certified</b>	Thermostat OSB panels are Home Innovation NGBS Green Certified for Resource Efficiency, Energy Efficiency and Indoor Environmental Quality. Please visit <a href="http://Homeinnovation.com/Green">Homeinnovation.com/Green</a> for more information.
<b>Formaldehyde Content</b>	Thermostat OSB panels contain no added urea formaldehyde resins. Emission levels for certified PS 1 and PS 2 structural panels are exempt by the California Air Resources Board in the <i>Composite Wood Air Toxic Control Measure (ATCM)</i> and phenolic bonded structural panels are exempt from testing or monitoring by HUD in the <i>Manufactured Home Construction and Safety Standards</i> .





# Specifications— Thermostat® OSB Radiant Barrier

## Manufacturing Locations

Location	APA Mill Number	Zip Code	Harvest Radius
Allendale, SC	515	29827	50 miles
Fordyce, AR	311	71742	100 miles
Hosford, FL	310	32334	75 miles



## Georgia-Pacific

Georgia-Pacific Wood Products  
133 Peachtree St., N.E.  
Atlanta, GA 30303  
800-284-5347 [www.builditbetter.com](http://www.builditbetter.com)

Thermostat, Georgia-Pacific and the Thermostat and Georgia-Pacific logos are trademarks owned by or licensed to Georgia-Pacific Wood Products LLC. Sustainable Forestry Initiative, SFI, and SFI logo are trademarks of Sustainable Forestry Initiative, Inc. The Home Innovation NGBS Green Certified logo is a trademark of Home Innovation Research Labs.  
©2013 Georgia-Pacific Wood Products LLC. All rights reserved. 9/13 GP-TM Lit. Item #621647.