

# Forté® Centerset Bathroom Sink Faucet K-10270-4A

### **Features**

- 5-1/8" (130 mm) spout reach.
- 1.2 gal/min (4.5 l/min) maximum flow rate [max at 60 psi (4.14 bar)]
- KOHLER ceramic disc valves exceed industry longevity standards for a lifetime of durable performance.
- Two traditional lever handle centerset bathroom sink faucet for 4" centers.
- Includes metal pop-up drain with 1-1/4" tailpiece.
- Reversible quarter-turn washerless ceramic disc valves.
- Coordinates with Forte faucets, accessories, and showering components to complete your bathroom.
- Low-flow aerator available (please see latest price book)

### Material

- Premium Metal Construction
- KOHLER finishes resist corrosion and tarnishing.


### Installation

- Deck-mount installation.
- For 4" (102 mm) centers.
- Integrated supply lines with 3/8"compression connection.

### **Optional Accessories**

1160595 .35 gpm Aerator, Medium





### Codes/Standards

ASME A112.18.1/CSA B125.1

NSF 61

ADA

NSF 372

All applicable US Federal and State material regulations

DOE - Energy Policy Act 1992

EPA WaterSense®

California Energy Commission (CEC)

ADA

ICC/ANSI A117.1

CSA B651

**OBC** 

## KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.

### Available Color/Finishes


Color tiles intended for reference only.

Color	Code	Description
	CP	Polished Chrome
	G	Brushed Chrome
	BN	Vibrant® Brushed Nickel





# Forté® Centerset Bathroom Sink Faucet K-10270-4A



### **Technical Information**

All product dimensions are nominal.

Drain included: YES
Drain tailpiece YES

included: **Spout:** 

Spout reach: 5-1/8" (130 mm) Handle clearance: 4" (102 mm)

Faucet:

Flow rate: 1.5 gal/min (5.7 l/min)

### **Notes**

Install this product according to the installation guide.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

