
THERMOSTATIC TEMPERATURE Thermostat bath valve MODEL # 34521

Pure Freude an Wasser



GROHE America, Inc | 200 North Gary Avenue, Suite G, Roselle, IL 60172 Phone: +1 (800) 444-7643 | Fax: +1 (800) 225-2778 | us-customerservice@grohe.com





ADA_

Product Description: Thermostat bath valve

Standard Specification:

- GROHE CoolTouch® safety housing
- GROHE StarLight® finish
- GROHE TurboStat® C3 compact cartridge

with wax thermoelement

1/2" ceramic cartridge (180° turn)

- GROHE AquaDimmer Eco with multi-function: Flow control, Bath/Shower diverter and integrated GROHE EcoButton
- Volume control
- Bath/shower diverter
- SafeStop at 100°F
- Includes metal shelving system
- Switch between hand shower and shower head shower via built-in diverter
- Adjustable volume control through diverter (GROHE AquaDimmer®)
- 12 ½" Width
- 6 ¾" Spout Reach
- Cascade water delivery through tub spout
- 6" distance between hot and cold water inlet
- Tub Spout Flow Rate: 5.3 gpm (20 L/min) at 45 PSI
- ½" outlet for connection to a shower hose

Applicable Codes & Standards:

- Energy Policy Act of 1992
- ASME A112.18.1/CSA B125.1
- ICC/ANSI A117.1

Color:

□ 34521 001 chrome