

RXL5 LED Exit Sign



Royal Pacific Ltd.

4931 Paseo Del Norte NE
Albuquerque, NM 87113
Ph: 1-800-937-6925
Fax: 1-888-207-9509

EXIT SIGN



GENERAL DESCRIPTION

LED exit sign.

MAIN FEATURES

Listing

- ETL listed for damp location.

Voltage

- Dual 120/277V

Lamps

- LED
- Energy consumption 2 watts for red letters, 1 watt for green letters.
- Estimated 25 year life.

Battery

- One
- 4.8V
- Nickel-Cadmium
- Protected from deep discharge by automatic low voltage disconnect circuitry.
- Whenever normal AC current fails, the internal solid state transfer switch automatically connects the internal battery to the fixture to keep the sign continuously lit for at least 90 minutes.

Operating Temperature

- 10°C (50°F) to 40°C (104°F).

Housing

- High impact thermoplastic.
- Flame retardant.
- Single or double face.
 - Two lettered faces.
 - One blank face.
- Universal snap-in and out chevron design meets all state and local codes (UL924).

Mounting

- Wall
- Ceiling

Finish / Color Options

- Green letters w/white housing.
- Red letters w/white housing.

Other Features

- Integral recharging system.
- Fully automatic operation.
- Completely self contained.
- Compact, low profile design.
- Limited 5 year warranty.
- Momentary test switch.

Project:
Contact:
Location:
Fixture Type:

Quantity	Remarks