

Features

- Solid brass body
- Ceramic disc cartridge
- Single lever handle.
- 180 degree swivel spout
- Installation in a 1-3/8" hole
- 1-1/2" maximum deck thickness
- High arc spout with pull-out spray head
- Dual function ABS pull-out spray head - aerated stream or spray
- Magnetic docking keeps the pull-out spray head firmly in place with an integrated magnet, so it stays docked when not in use
- 1.8 gpm max. (6.8L/min) @ 60psi - saves 20% more water
- Flexible supply lines with 3/8" compression fittings

Optional Accessories

- T3600 soap dispenser.

Warranty

- Lifetime Limited Warranty for residential use
- 5 Year Limited Warranty for commercial use



Specified Model

Model	T3540
Faucet Height	16 ¹⁷ / ₅₀ " (415 mm)
Spout Reach	9 ¹ / ₂₀ " (230 mm)
Deck to Aerator	8 ³³ / ₅₀ " (220 mm)
Flow Rate	1.8 gpm max (6.8L/min) @ 60 psi
Shipping Weight	9 lbs.
Material	brass construction
Installation	deck mount, single hole

To Be Specified:

	Finish
<input type="checkbox"/>	PC Polished Chrome
<input type="checkbox"/>	LS Luxe Stainless

Codes/Standards

Certified to CUPC
 Certified to AB1953
 Certified to NSF/ANSI 61
 Complies with Federal Lead Plumbing Law as certified with IAMPO R&T inc.
 ADA compliant for lever handle



Notes

Install this product according to the installation instructions.

