

BANCROFT_®

Features

- Acrylic
- 122 BubbleMassage™ airjets
- With Zones of Control™ feature
- Drop-in
- Blower motor with 300 W heater and electronic back-lit user control
- Available with chromatherapy lights [-GCR]
- · Complements the Bancroft Suite
- 66" (167.6 cm) x 42" (106.7 cm) x 22" (55.9 cm)


Codes/Standards Applicable

Specified model meets or exceeds the following:

- ANSI Z124.1.2
- IAPMO/UPC IGC 171
- UL 1795

5.5' BUBBLEMASSAGETM BATH

K-1158-GCR



Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Accessories

- CP: Polished Chrome
- PB: Vibrant_® Polished Brass
- NA: None applicable

Specified Model

•						
Model	Description		Colors/Finishes			
K-1158-G	5.5' BubbleMassage bath – less chromatherapy	□ 0		☐ Other		
K-1158-GCR	5.5' BubbleMassage bath – with chromatherapy (shown)					☐ Other
Recommend	led Accessories					
K-7161-AF	-7161-AF Adjustable pop-up drain			□ CP	□ PB	☐ Other
Optional Ac	cessories			<u> </u>		
K-1491	Pillow		□ 0			☐ Other
K-1601	Footstop		□ 0			☐ Other
K-1705	Remote control	□NA				
K-9498	3" (7.6 cm) whirlpool keypad trim			□ CP	□ PB	☐ Other

Product Specification

The acrylic 5.5' BubbleMassage bath shall be 66" (167.6 cm) in length, 42" (106.7 cm) in width, and 22" (55.9 cm) in height. Product shall have a blower motor with 300 W heater and electronic back-lit user control. Product shall be for drop-in installation. Product shall have Zones of Control feature and 122 BubbleMassage airjets. Product shall be available with chromatherapy lights [-GCR]. Product shall complement the Bancroft Suite. Bubblemassage bath shall be Kohler Model K-1158-____-

BANCROFT®

Technical Information

motor:

Fixture*:						
Bathing well:						
Basin area, bottom	46" (116.8 cm) x 30" (76.2 cm)					
Basin area, top	57" (144.8 cm) x 34" (86.4 cm)					
Weight	130 lbs (59 kg)					
To overflow:						
Water depth	16" (40.6 cm)					
Capacity	95 gal (359.6 L)					
* Approximate measurements for comparison only.						

Included component:										
Cut-out templa	1043292-7									
Blower	Heater	Τ,	/	Hz		Δ				

220-240

300 W

3

50/60

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):

Blower motor/control 220-240 V, 15 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.

Hot water supply should be 70% of capacity or greater. Installations will vary.

This bath is designed for drop-in installation only. It is not suited for use in a three-wall alcove with an overhead shower.

A blower motor/control access panel is required.

Floor support under the bath must provide for a minimum of 50 lbs/square foot (242 kg/square meter) loading.

