

# Get Ready to Roll

See Reverse for  
More Information ▶

Coming to select  
Lowe's stores  
May 2017



## TEC® Skill Set™ Roll-On Vinyl Tile & Plank Adhesive



This breakthrough innovation eliminates hard-on-the-knees troweling and tedious spraying. TEC® Skill Set™ Roll-On Vinyl Tile & Plank Adhesive allows installers to stand up and easily apply adhesive with a paint roller. It's formulated using installer-friendly technology for easy handling, application, and clean up to reduce fatigue. TEC® Skill Set™ Roll-On Vinyl Tile & Plank Adhesive allows the installation of LVT, LVP and vinyl sheetgoods\* in 20 to 30 minutes—so your team is ready to rock and roll.

**Turn to TEC® Skill Set™ Roll-On Vinyl Tile & Plank Adhesive for a roller-applied, installer-friendly adhesive for LVT and LVP installations.**

\*Do not use with fiberglass-backed vinyl sheetgoods, nor directly over peel and stick tile.  
Not recommended for use with felt-backed or mineral-backed vinyl sheetgoods, linoleum or rubber.





# TEC® Skill Set™ Roll-On Vinyl Tile & Plank Adhesive

This breakthrough, user-friendly adhesive is ideal for luxury vinyl tile, luxury vinyl plank and solid vinyl heterogeneous or homogeneous sheetgoods\*. This unique, low odor formulation dries quickly, provides a long open time and is easy to clean up.

\*Do not use with fiberglass-backed vinyl sheetgoods, nor directly over peel and stick tile. Not recommended for use with felt-backed or mineral-backed vinyl sheetgoods, linoleum or rubber.



Pour adhesive



Roll-on adhesive



Install flooring in 20-30 minutes

## Features and Benefits

- Moisture and alkali resistant up to 90% RH / 10 lbs. MVER and 7-11 pH
- Extended open time (4-6 hours)
- Heat weld after 60 minutes
- Exceptional coverage at 190-200 sq ft/70 fl. oz. (17.7-18.6 m<sup>2</sup>/2.07 L) with 3/8" nap roller
- Solvent free and low VOC (VOC <1 g/L)
- LEED® Compliant and CRI Green Label Plus Certified

## Coverage

Coverage will vary with the absorption rate (porosity) and surface profile of the substrate. With just one coat of Roll-On Vinyl Tile & Plank Adhesive, you can lay down the amount of adhesive needed for the specific vinyl flooring being installed.

Figures below are presented only as guidelines.

Recommended Roller Size	Approximate Coverage
3/8" Nap Roller	190-200 ft <sup>2</sup> /70 fl. oz. (17.7-18.6 m <sup>2</sup> /2.07 L)

## Packaging

70 fl. oz. plastic jug (2.07 L)



## Suitable Substrates

When properly prepared, suitable substrates include:

- Concrete (all grade levels)
- Underlayment grade plywood
- Gypsum substrates (properly prepared)

## Technical Data

### Physical Properties

Description	
Base	Polymer latex
Physical State	Thin paste
Color	Off white
Open Time	4-6 hours depending on substrate porosity
VOC/Liter of Material	<1 gram (calculated)
Freeze/Thaw Stability	Stable for 3 cycles at 10°F (-12°C)
Storage	For optimal shelf life, store at a moderate room temperature, in closed containers, and protect this adhesive from freezing. If frozen, allow to return to room temperature slowly and stir before use. Avoid prolonged or repeated freeze thaw cycles.
Shelf Life	Maximum 1 year from date of manufacture in unopened package.

©Copyright 2017 H.B. Fuller Construction Products Inc.

TEC® Skill Set™ is a trademark of H.B. Fuller Construction Products Inc.

LEED® is a registered trademark of U.S. Green Building Council.

Form# ROVTPASSN0317-20



©Copyright 2017 Lowe's Companies, Inc. All rights reserved. Lowe's and the gable design are registered trademarks of LF, LLC.