


<b>Type of Appliance</b>	Condensing, Tankless, Temperature controlled, continuous flow, gas hot water system, Energy Star Qualified
<b>Rinnai model number</b>	REU-KCM2025FFU-US
<b>Operation / Installation</b>	Forced combustion; indoor only; Certified for installation in Manufactured (Mobile) Homes
<b>Minimum/Maximum Gas Rate (Input)</b>	10,300 - 130,000 BTU/h
<b>Electrical</b>	Appliance: AC 120 Volts - 60 Hz Temperature Controller: DC 12 Volts
<b>Electrical Consumption</b>	Normal: 89 w Standby: 1.3 w Anti-frost protection: 167 w
<b>Amperage</b>	Max: 2.3A Fuse: 10A
<b>Ignition System</b>	Direct electronic ignition
<b>Hot Water Capacity</b>	Minimum flow rate: 0.26 GPM (1 l/min) Minimum activation flow rate: 0.4 GPM (1.5 l/min) Maximum flow rate: 6.5 GPM (24.6 l/min)
<b>Temperature (with remote)</b>	120° - 140° F (49° - 60°C)
<b>Temperature (without remote)</b>	120° F (49°C), 125° F (49°C), 135° F (57°C), or 140° F (60°C)
<b>Approved Gas Types</b>	Natural or Propane (ensure unit matches gas type)
<b>Energy Factor (EF)</b>	Natural Gas: 0.93 Propane: 0.93
<b>Service Connections</b>	Gas supply: 3/4 inch (19mm) MNPT Cold water inlet: 3/4 inch (19mm) MNPT Hot water outlet: 3/4 inch (19mm) MNPT
<b>Water Flow Control</b>	Water flow sensor, electronic water control and fixed by-pass
<b>Minimum/Maximum Water Supply Pressure</b>	20 - 150 PSI (138-1035 KPa) ( recommended 60 - 80 PSI (414 - 552 KPa) for optimal performance)
<b>High Altitude Capability</b>	Up to 5,400 ft (1646 m) elevation above sea level

*Rinnai is continually updating and improving products; therefore, specifications are subject to change without prior notice. Local, state, provincial and federal codes must be adhered to prior to installation.*



## Controller (Optional)

MC-91-2US (optional maximum of 4 can be installed)  
Do not install MC-100V-1US or BC-100V-1US

## Controller Cable

Non-polarized two-core cable, minimum 22 AWG

## Safety Devices

- Flame failure - Flame Rod
- Boiling protection
- Combustion fan rpm check
- Over current - glass fuse
- Remaining flame (OHS)
- Thermal fuse
- Automatic frost protection

## Clearances from Combustibles

\* 24 inches (610mm) required for service

- Top of heater - 6 inches (152mm)
- Front of heater - 6 inches \*(152mm)
- Sides of heater - 2 inches (51mm)
- Back of heater - 0 inches
- Bottom of heater - 12 inches (305mm)
- From vent pipe - 0 inches

## Clearances from Non-combustibles

\* 24 inches (610mm) required for service

- Top of heater - 2 inches (51mm)
- Front of heater - 6 inches \*(152mm)
- Sides of heater - 1/2 inches (13mm)
- Back of heater - 0 inches
- Bottom of heater - 12 inches (305mm)
- From vent pipe - 0 inches

## Min. / Max. Gas Supply Pressure

Natural Gas: min 4" W.C. (2.5mbar) max 10.5" W.C. (26.1mbar)  
Propane Gas: min 8" W.C. (20mbar) max 13.5" W.C. (33.6mbar)

## Manifold Gas Pressure (inches W.C.)

Natural Gas: high fire 2.27" W.C. (5.7mbar) low fire 1.00" W.C. (2.5mbar)  
Propane Gas: high fire 2.58" W.C. (6.4mbar) low fire 1.08" W.C. (2.7mbar)

## NOx

Complies with South Coast Air Quality Management District 14 ng/J or 20 ppm NOx emission levels

## Venting

Direct Vent system designed for use with Ubbink Polypropylene Concentric Vent, Twin Pipe PVC/CPVC (3" and 4" configurations), or Centrotherm 3" Polypropylene (with Centrotherm Twin Pipe Adapter) [See installation and operation manual for details regarding installation and allowed vent lengths.](#)

## Limited Warranty

Heat exchanger: 12 years\* for residential, All other parts: 5 years\*; Labor: 1 year;  
(\* 3 years if used as a circulating water heater within a circulation loop, when the water heater is in series with a circulation system and all circulating water flows through the water heater, and where an aquastat / thermostat, timer, or an on-demand recirculation system is not incorporated.)  
Refer to the manual for complete warranty information.

