

**ACTICLEAN™ HET RIGHT HEIGHT®
ELONGATED COMPLETE TOILET**

714AA.151

- Self-Cleaning toilet bowl that cleans and removes stains with a simple press of a button.
- **Two Bowl Cleaning Cycles:**
 - **Quick Clean** is best used for regular upkeep in between deep cleanings. A Quick Clean cycle will clean the inside of the toilet bowl in just one minute.
 - **Deep Clean** completely and thoroughly cleans the inside of the toilet bowl in 10 minutes. The result is a fresh scented, sparkling clean bowl!
- Battery Operated Cleaning System: 4AA batteries (included) give you up to 1 year of battery life
- Includes VorMax™ Flush Technology to help maintain a tidy bowl in between ActiClean cleanings Δ
- CleanCurve™ Rim eliminates the rim area where dirt and buildup hide
- EverClean® surface inhibits the growth of stain- and odor-causing bacteria, mold and mildew on the surface
- Vitreous china
- High efficiency (4.8 Lpf/1.28 gpf) toilet
- Meets EPA WaterSense® criteria
- 12" (305mm) rough-in
- Comfortable 16-1/2" rim height for ADA accessible applications
- Superior solid waste removal with 1,000g MaP Score** and a 2-1/16" fully glazed trapway
- Generous 9" x 8" water surface area
- 1-3/4" Dual Injection Flush Valves for optimal bowl rinsing
- Easy Installation. Everything needed for toilet installation is included and can be hand tightened
- Chrome handle (alternative finishes available)
- Robust plastic seat features no slip bumpers and a release button that allows you to remove the seat for quick and easy cleaning
- 2 color-matched bolt hole covers
- 100% factory flush tested
- Lifetime warranty on chinaware, 10 year warranty on mechanical parts, 1 year on electronics and 1 year warranty on seat

Nominal Dimensions (with Lid CLOSED):

30-3/16" x 20-11/16" x 31-3/8"
(767 x 526 x 797mm)

Nominal Dimensions (with Lid OPEN):

30-3/16" x 20-11/16" x 40"
(767 x 526 x 1016mm)

Fixture, toilet seat, wax ring, and bowl bolts only.
Supply line not included.

Compliance Certifications -

Meets or Exceeds the Following Specifications:

- ASME A112.19.2/CSA B45.1 for Vitreous China Fixtures
- US EPA WaterSense® Specification for HET's

** Maximum Performance (MaP) testing performed by IAPMO R&T Lab. MaP Report conducted by Veritec Consulting, Inc. and Koeller and Company.



SELF-CLEANING TANK TOP DEVICE

SEE REVERSE FOR ADDITIONAL
ROUGHING-IN DIMENSIONS

To Be Specified:

- Color: White
- Supply with stop:

EVERCLEAN®
Surface



Δ **Source:** IAPMO R&T Labs Test Report No.109-141486-002, comparing VorMax™ against conventional under-the-rim-water-dispersal toilets from major retailers.



MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ICC ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE BUILDING FACILITIES-CHECK LOCAL CODES.

