QUICK REFERENCE GUIDE

OB30DTEPX3

30" DOUBLE SELF-CLEAN BUILT-IN OVEN



Designed for ultimate performance and cooking capability, the 30" Built-in Oven features 10 cooking functions, a self-cleaning mode and a catalytic smoke eliminator. Finished in stainless steel and reflective glass, it blends refined design with durability — matching the Fisher & Paykel family of kitchen appliances.



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support
T 1.888.936.7872 W fisherpaykel.com

FEATURES & BENEFITS

SKU

UPC

Perfect Results	The powerful 4400W broiler gives even browning
	results, and the AeroTech™ cooking system circulates
	air providing even heat distribution, eliminating hot
	spots and making multi-shelf cooking ideal. The
	two-step roast program helps you produce a
	perfectly tender and juicy roast.
Sized to Suit	Each oven has 4.1 cu. ft. of total capacity and is big
	enough to cook a turkey and a large tray of roast
	vegetables.
Designed to Match	Finished in black reflective glass and stainless steel,
	this durable oven is designed to match the rest of
	Fisher & Paykel's coordinated kitchen family.
Easy Cleaning	No need for harsh chemical cleaners in our ovens;
	simply remove the racks and set to self-clean.
Precise Control	Temperature adjustment is easy with smooth,
	balanced dial movement. Sophisticated electronics
	then maintain an even, accurate temperature for
	better, more precise results.
Safe and Sound	CoolTouch doors are safer and improve energy
	efficiency by keeping the heat on the inside. An
	advanced heat-reflective coating and innovative
	cooling system keeps heat where it should be.
Oven Functions	Oven functions include: Bake, Aero™ Bake, True
	Aero™, Broil, Maxi Broil, Aero™ Broil, Aero™ Pastry,
	Roast, Classic Bake, Warm, Self-clean
Accessories	Telescopic sliding shelves, (5 Sets - additional sets
	available for purchase), 3-pc anti-splatter grill system
	(Pan, Grid & Rack), Meat probe.

84720

822843847204

SPECIFICATIONS

Finish	Black reflective glass & brushed stainless steel	
Dimensions inches	H48 7/16" x W29 29/32" x D23 29/32" 4.1 cu. ft. + 4.1 cu. ft.	
Total capacity +		
Shelf positions	8 per cavity	
Oven Functions	11	
Performance		
Broil	4400W	
AeroTech™ cooking system	•	
Automatic rapid pre-heat	•	
Controls		
Electronic clock	•	
Automatic cooking/minute timer	•	
Precise electronic temperature control	•	
Automatic pre-set temperatures	•	
Capacitive touch controls	•	
Illuminated halo dials	•	
Interior light	3 x 20W per cavity (halogen)	
Audio feedback	•	
Fahrenheit/Celsius temperature	•	
Sabbath mode	•	
Power requirements		
Supply voltage	120 - 240V	
Supply frequency	60Hz	
AMP draw	38.3A 240V 33.7A 208V	
Manufacturer's warranty	2 years	

For full specifications visit fisherpaykel.com

DATA SHEET

0 0 22 13/32" 0 0 I DATUM : FRONT OF CARCASS PLAN VIEW **B** 29 29/32" :0 \circ 0000 0 A 48 1/2" 0 Ø 6 6 6 6 6 6 0 FRONT VIEW PROFILE VIEW

30" DOUBLE SELF-CLEAN BUILT-IN OVEN

Model no:

OB30DTEPX3

Product Dimensions	
Overall height* of oven	48 1/2
Overall width of oven	29 29/32
© Depth of oven front and control panel** (excludes handle and dials)	1 17/32
Depth of oven chassis (does not include oven front)	22 13/32
Height from bottom datum to top of stainless fascia cap	45 9/16
F Height from bottom datum to bottom of stainless fascia cap	43 25/32
Height from bottom datum to top of top door	43 5/16
Height from bottom datum to centre of top handle	41 31/32
Height from bottom datum to bottom of top door	22 17/32
Height from bottom datum to top of bottom door	21 15/16
Height from bottom datum to centre of bottom handle	20 19/32
© Height from bottom datum to top of vent	1 5/32
M Thickness of handle	5/8'
Neight of chassis	47 15/16
Depth of door (open) (measured from front of door)	20 7/8
Overall width of chassis	28 11/32
Width of handle	28 5/8
Depth of handle (measured from front of door)	1 21/32

^{*} All height measurements included mounted feet

^{**} Measured to front glass surface and excludes 3/32" stainless cap

Minimum Clearances	in
Minimum inside height of cavity from bottom datum	48 3/16"
Minimum inside width of cavity	28 1/2"
Minimum inside depth of cavity from front datum	22 5/8"

INDICATES CABINETRY CARCASS DATUM ------INDICATES MINIMUM CABINETRY CLEARANCES ------

DATE: 11.06.2015

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ± 2 mm (3/32"). Please read the installation manual for detailed information on installing the product. www.fisherpaykel.com