

## QUICK REFERENCE GUIDE

DD24DI7

# PANEL-READY DOUBLE DISHDRAWER™ DISHWASHER



Designed to fit existing kitchen cabinetry, this Double DishDrawer™ dishwasher has comparable dimensions to those of traditional dishwashers but provides the benefit of two independent drawers for added convenience and ergonomics. This panel-ready model can be integrated seamlessly into your kitchen cabinetry.



### A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 W [fisherpaykel.com](http://fisherpaykel.com)

## FEATURES & BENEFITS

<b>Independent Drawers</b>	The Double DishDrawer™ dishwasher fits seven place settings per drawer and provides ultimate convenience as one drawer can be washing as you fill the other. DishDrawer™ dishwashers allow flexible design options and good ergonomics in the kitchen. The double drawers can be used together or one at a time allowing you match the wash program to the exact load type in each drawer.
<b>Superior Cleaning</b>	Unique SmartDrive™ technology has few moving parts, resulting in greater reliability. The pump brings water into the spray arm, which rotates at different speeds depending on the wash cycle selected, to deliver a superior clean and better dish care.
<b>Nine Wash Options</b>	This DishDrawer™ dishwasher features nine essential wash programs: Rinse, Fast, Delicate, Normal Eco, Normal and Heavy. The range of settings enables this DishDrawer™ dishwasher to wash everything from fine glass and crystal to heavily soiled pots and pans at the touch of a button. A single control interface provides simple program selection and operation, while the 'delay' start setting means the dishes can be done when it's most convenient.
<b>Reliable Filtration</b>	One of the challenges in all dishwashers is a robust filter system that removes debris and avoids blocking. This DishDrawer™ dishwasher has a 3 stage filtration process with removable components for easy and hygienic cleaning.
<b>Simple Racking System</b>	DishDrawer™ dishwashers have simple and useful racking options. The cutlery basket can be customized for different utensils. Cup racks and tines can be folded flat to accommodate pots or upwards to hold glassware. Wine glass holders ensure that short and long stemmed glasses are secure throughout the wash.

<b>SKU Code</b>	84692
<b>UPC Code</b>	822843846926

## SPECIFICATIONS

<b>Finish</b>	Integrated (apply your own cabinetry façade)
<b>Dimensions (excluding handles)</b>	H32 9/32 - 34 21/32" x W23 19/32" x D22 13/32 - 22 9/16"
<b>Energy Star Certified</b>	●
<b>Energy usage (kWh per year)</b>	276
<b>Water usage</b>	2 gallons per drawer
<b>Performance</b>	
SmartDrive™ technology	●
Fan assisted drying	●
<b>Capacity and loading</b>	
Place settings per drawer	7
Flexible racking system	●
Fold down & pitch adjustable tines	●
Fold down & height adjustable cup racks	●
Accommodates plates up to	11 1/2"
<b>Wash programs</b>	9
Genuine half load wash option	●
Eco options	●
<b>Safety</b>	
Three stage total flood protection	●
<b>Controls</b>	
Wireless remote	●
<b>Power requirements</b>	
Supply voltage	110 - 120V
Supply frequency	60Hz
AMP draw	10.6A
<b>Accessories</b>	
Cutlery basket	2
Knife clip	2
<b>Manufacturer's warranty</b>	1 year

For full specifications visit [fisherpaykel.com](http://fisherpaykel.com)

**Fisher & Paykel**

**DATA SHEET**

**24" DOUBLE DISHDRAWER™ DISHWASHER**

Model no:

**DD24DI7**

Product Dimensions	in
Ⓐ Overall height* of DishDrawer™ dishwasher	32 9/32" - 34 21/32"
Ⓑ Overall width of DishDrawer™ dishwasher	23 19/32"
Ⓒ Depth of DishDrawer™ dishwasher chassis**	21 25/32"
Ⓓ Minimum height from top datum to bottom of bottom drawer	28 7/16"
Ⓔ Height from top datum to top of bottom drawer	16 7/32"
Ⓕ Minimum height from top datum to bottom of top drawer	15 29/32"
Ⓖ Ventilation gap between custom panels	5/16"
Ⓗ Minimum height of lower drawer panel	12 1/4"
Ⓚ Height of chassis at rear (not including mounted feet)	31 15/16"
Ⓛ Height of mounted feet (adjustable)	11/32" - 2 23/32"
Ⓜ Height of toekick panel (adjustable)	2 3/4" - 4 23/32"
Ⓝ Depth of toekick panel***(adjustable)	1 3/16" - 3 11/32"
Ⓞ Depth of drawer (open) (measured from front datum)**	20 3/4"

\* Includes adjustable mounted feet and the range of movement.

\*\* Does not include the custom drawer panels, handles or toekick panel to be manufactured and fitted by cabinetmaker.

\*\*\* Does not include the custom toekick panel to be manufactured and fitted by cabinetmaker. If the toekick depth is greater than 1-33/32", the panel will need to be cut to clear the underside of the tub, please refer to the installation manual for more detail.

Note: Service outlet at rear extends both sides, hoses and cords can be routed to either or both.

Minimum Clearances	in
Minimum inside height of cavity from bottom datum	32 9/32"
Minimum inside width of cavity	23 5/8"
Minimum inside depth of cavity from front datum	22 1/16"
Minimum ventilation gap between front panels	5/16"
Minimum clearance from bottom of toekick panel to floor	15/32"

INDICATES CABINETRY CARCASS DATUM - - - - -  
 INDICATES MINIMUM CABINETRY CLEARANCES - - - - -

DATE: 19.08.2015

IMPORTANT NOTE: Throughout this guide, dimensions may vary by ±2mm (±3/32"). Please read the installation manual for detailed information on installing the product. [www.fisherpaykel.com](http://www.fisherpaykel.com)

