







24" (61 cm) and 27" (69 cm) Electric Washer/Dryer

PRODUCT MODEL NUMBERS
WET4024E, WET4027E


Dimensions/Clearances - 24" (61 cm)



Dimensions/Clearances - 27" (69 cm)



Clearances




ELECTRICAL REQUIREMENTS

To supply the required 3 or 4 wire, single phase, 120/240 volt, 60 Hz., AC only electrical supply (or 3 or 4 wire, 120/208 volt electrical supply, if specified on the serial/rating plate) on a separate 30-amp circuit, fused on both sides of the line. A time-delay fuse or circuit breaker is recommended. Connect to an individual branch circuit.


VENTING REQUIREMENTS

Exhaust venting: Exhaust your dryer to the outside. 4" (102 mm) diameter vent is required. Rigid or flexible metal exhaust vent must be used. Do not use plastic or metal foil vet. Exhaust hood must be at least 12" (305 mm) from the ground or any object that may be in the path of the exhaust.

Recommended Styles:




Louvered hood



Box hood

Acceptable Style:



Angled hood

The "Vent System Chart" provides venting requirements that will help achieve best drying performance.

Vent System Chart, 24" Models

| Number of 90° turns or elbows | Type of vent | Box/louvered hoods | Angled hoods |
|-------------------------------|--------------|--------------------|-----------------|
| 0 | Rigid metal | 43 ft. (13.1 m) | 36 ft. (11.0 m) |
| 1 | Rigid metal | 33 ft. (10.1 m) | 26 ft. (7.9 m) |
| 2 | Rigid metal | 23 ft. (7.0 m) | 16 ft. (4.9 m) |

Vent System Chart, 27" Models

| Number of 90° turns or elbows | Type of vent | Box/louvered hoods | Angled hoods |
|-------------------------------|--------------|--------------------|-----------------|
| 0 | Rigid metal | 37 ft. (11.3 m) | 35 ft. (10.7 m) |
| 1 | Rigid metal | 32 ft. (9.7 m) | 27 ft. (8.2 m) |
| 2 | Rigid metal | 23 ft. (7.0 m) | 19 ft. (5.8 m) |


NOTE: Side exhaust installations have a 90° turn inside the dryer. To determine maximum exhaust length, add one 90° turn to the chart.

DRAIN SYSTEM

Drain system can be installed using a floor drain, wall standpipe, floor standpipe, or laundry tub. Select method you need.


Floor standpipe drain system

Minimum diameter for a standpipe drain: 2" (51 mm). Minimum carry-away capacity: 17 gal. (64 L) per minute. Top of standpipe must be at least 39" (990 mm) high; install no higher than 96" (2.4 m) from bottom of washer/dryer. If you must install higher than 96" (2.4 m), you will need a sump pump system.




Wall standpipe drain system

See requirements for floor standpipe drain system.



Floor drain system

Floor drain system requires a Siphon Break Kit (Part Number 285834), 2 Connector Kits (Part Number 285385), and an Extension Drain Hose (Part Number 285863) that may be purchased separately. See "Use and Care Guide" for ordering details. Minimum siphon break: 28" (710 mm) from bottom of washer/dryer. (Additional hoses may be needed.)



Laundry tub drain system

Minimum capacity: 20 gal. (76 L). Top of laundry tub must be at least 39" (990 mm) above floor; install no higher than 96" (2.4 m) from bottom of washer/dryer.

IMPORTANT: To avoid siphoning, no more than 4.5" (113 mm) of drain hose should be inside standpipe or below the top of wash tub. Secure drain hose with shipping strap.

