

A KOHLER COMPANY

Features

- Compression molded from our exclusive solid Vikrell® material
- Modular 4-piece design
- Pivot "snap together" installation
- Caulkless seam installation
- Durable high-gloss finish
- Not recommended as a bath only installation
- 10-year consumer/3-year commercial limited warranty
- Grab bars constructed from anodized aluminum are provided unattached
- 20" (508 mm) bath depth (floor to top of threshold)
- 60-1/4" (1530 mm) x 37-1/4" (946 mm) x 77-1/2" (1969 mm) complete unit rough-in dimensions include flanges
- 60" (1524 mm) x 36" (914 mm) x 76-1/4" (1937 mm) complete unit finished dimensions

Codes/Standards Applicable


Specified model meets or exceeds the following:

- ASTM E162
- ASTM E662
- CSA B45.5/IAPMO Z124

60" BATH AND WALL SURROUND **WITH GRAB BARS** 7116011



MATERIAL STRENGTH. PROVEN PERFORMANCE,



Colors/Finishes

- 0: White
- N: Nickel
- V: Matte Silver
- Other: Refer to Price Book for additional colors/finishes

Specified Model

Model	Complete Unit Description	Grab Bar Finishes		Fixture Colors		
71160113	60" bath and wall surround with grab bars - left drain	□N	□V	□ Other	0	□ Other
71160123	60" bath and wall surround with grab bars - right drain	□N	□V	□ Other	0	☐ Other

ACCORD®

Technical Information

Fixture*:						
Bathing well:						
Basin area	22-7/8" (581 mm) x 46" (1168 mm)					
Top area	24-7/8" (632 mm) x 50-7/8" (1292 mm)					
To overflow:						
Water depth	15-1/8" (384 mm)					
Capacity	70 gal (263.5 L)					
* Approximate measurements for comparison only.						

Model	Door maximum width	Door maximum height
71160113 71160123	56-3/4" (1441 mm)	55-7/8" (1419 mm)

Installation Notes

Install this product according to the installation guide.

Size the drain cutout to fit the drain assembly that will be used.

End stud positioning is critical.

Studs should be positioned roughly as shown.

Bath cannot be installed without the wall surround.

