



THIS IS GREENFIBER® LOOSE FILL FORMULA INSULATION

Application Coverage Chart
Dry install only. Do not add water. **30 lbs (13.6 kg) INS515LD**

R-Value at 75° F Mean Temp. Valor de resistencia térmica (valor R) a 75 F de temperatura media	Minimum Thickness (inches) Espesor mínimo (en pulgadas)		Net Coverage (no adjustment for framing) Cobertura neta (sin compensación para el entramado)			Net Coverage (adjusted for 2' x 6" framing on 16" centers) Cobertura neta (con compensación para una estructura de 2' x 6" en centros de 16")	
	Initial Installed Thickness Espesor inicial instalado	Settled Thickness Espesor asentado	Maximum Sq. Ft. per Bag Metros Cuadrado máximos por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad mínima de bolsas por 1,000 pies cuadrados	Minimum Weight per Sq. Ft. Peso mínimo por pie cuadrado	Maximum Sq. Ft. per Bag Metros Cuadrado máximos por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad mínima de bolsas por 1,000 pies cuadrados
	R 11	3.38	3.04	102.5	9.8	0.293	113.1
R 13	4.01	3.61	84.9	11.8	0.353	93.7	10.7
R 19	5.88	5.29	55.2	18.1	0.544	60.5	16.5
R 22	6.80	6.12	46.6	21.5	0.644	50.4	19.8
R 26	8.02	7.22	38.4	26.1	0.782	41.0	24.4
R 30	9.22	8.30	32.4	30.8	0.925	34.3	29.1
R 32	9.82	8.84	30.0	33.3	0.999	31.7	31.5
R 38	11.60	10.44	24.4	40.9	1.23	25.6	39.1
R 40	12.19	10.97	22.9	43.6	1.31	24.0	41.7
R 44	13.36	12.03	20.4	49.0	1.47	21.2	47.1
R 48	14.53	13.07	18.3	54.6	1.64	19.0	52.6
R 49	14.82	13.34	17.9	56.0	1.68	18.5	54.1
R 50	15.11	13.60	17.4	57.4	1.72	18.0	55.5
R 60	17.99	16.19	13.8	72.4	2.17	14.2	70.4

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF 30 LBS USING A VOLUMATIC III, 3rd GEAR AND 8" GATE. THE CHART IS BASED ON SETTLED THICKNESS AND IS FOR ESTIMATING PURPOSES ONLY. DO NOT EXCEED MAXIMUM SQUARE FEET COVERAGE PER BAG. THE APPLICATOR MUST INSTALL BOTH THE MINIMUM NUMBER OF BAGS PER 1000 SQ. FT. AND THE MINIMUM INSTALLED THICKNESS TO INSURE THE STATED R-VALUE HAS BEEN REACHED. FAILURE TO MEET BOTH THESE REQUIREMENTS MAY PREVENT THE APPLICATION OF SPECIFIED R-VALUE. THIS PRODUCT IS INTENDED FOR DRY APPLICATION ONLY. JOB CONDITIONS, APPLICATION TECHNIQUES, EQUIPMENT, AND SETTING CAN INFLUENCE ACTUAL COVERAGE. DO NOT ADD WATER TO THIS PRODUCT. MINIMUM NET WEIGHT IS 28.5 LBS.

Dry Dense Pack Sidewall Applications (3.5 pcf minimum installed density) 30 lbs. (13.6 kg) INS515LD

Thermal Resistance (R value) Resistencia térmica (R)	Framing Estructura	Installed Thickness (inches) Espesor instalado (pulgadas)	Minimum Wt. Per Square Foot lb/ft² Peso mínimo por pie cuadrado lb/ft²	Maximum Coverage Per Bag (No Adjustment for Framing) ft²/Bag Cobertura máxima por bolsa (sin compensación para la estructura)ft²/Bag	Maximum Coverage Per Bag (Adjusted for Framing) ft²/Bag Cobertura máxima por bolsa (con compensación para la estructura)ft²/Bag	
					(16" oc)	(24" oc)
13	2x4	3.5	1.02	29.39	32.4	31.3
21	2x6	5.5	1.60	18.70	20.6	19.9

THIS COVERAGE CHART IS FOR DRY APPLICATIONS ONLY AND IS BASED ON THE KRENDL KS200, WITH MATERIAL APPLIED DRY. FOR MAXIMUM COVERAGE PER BAG (ADJUSTED FOR FRAMING), THE FRAMING FACTOR FOR 16" OC STUD SPACING IS 9.375%; FOR 24" OC STUD SPACING THE FRAMING FACTOR IS 6.25%.

GreenFiber provides outstanding thermal performance, fire-resistance and sound control. Consisting of up to 85% recycled content, GreenFiber Insulation is specially treated for flame resistance.

R-value means resistance to heat flow - the higher the R-value, the greater the insulation power.

CERTIFICATION:

This insulation has been installed in conformance with the above recommendations, to provide a value of R-_____ using _____ bags of this insulation to cover _____ square feet of area.

Builder's Signature: _____

Company Name: _____

Date: _____

Applicator's Signature: _____

Company Name: _____

Date: _____

FOR MORE INFORMATION CONTACT:

GreenFiber Corporate Office
5500 77 Center Drive, Suite 100
Charlotte NC 28217

www.greenfiber.com

(p) 800.228.0024 (f) 704.379.0685
greenfiber.info@greenfiber.com

MANUFACTURING LOCATIONS:

Albany, NY
Belchertown, MA
Delphos, OH
Norfolk, NE
Chandler, AZ
Salt Lake City, UT
Tampa, FL
Waco, TX
Wilkes-Barre, PA

