

RUST-OLEUM®
SPECIALTY**SPECIALTY
VINYL SPRAYS****DESCRIPTION AND USES**

Rust-Oleum® Specialty Vinyl Sprays restore color on vinyl and fabrics. This coating is ideal for car and boat seats, dashboards, upholstery, luggage, furniture, sports equipment and more. Specialty Vinyl Sprays feature an advanced spray system that allows you to spray at any angle, even upside down for those hard to reach areas. A comfort spray tip with a wider finger pad to reduce fatigue caused by continuous spraying.

PRODUCTS

SKU	Description
1909830	Black
1911830	White

PAINTING CONDITIONS

Use outdoors or in a well ventilated area. Use when temperature is between 50-90°F (10-32°C) and humidity is below 85% to ensure proper drying. Do not apply to surfaces, when heated, exceed 200°F (93°C). Do not apply to galvanized steel. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

PRODUCT APPLICATION**SURFACE PREPARATION**

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry.

PRODUCT APPLICATION (cont.)**APPLICATION**

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Hold can upright 10-16" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can in motion while spraying. Keep the can the same distance from the surface. Apply two or more light coats a few minutes apart to avoid drips and runs. **Do not use near open flame.**

DRY & RECOAT

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 10 minutes, to handle in 1 hour and is fully dry in 24 hours. Wait at least 6 hours before sitting or using a painted object.

CLEAN-UP

Wipe off tip before storing. Clean-up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

TECHNICAL DATA

VINYL SPRAYS

PHYSICAL PROPERTIES

Physical Properties		VINYL SPRAYS
Resin Type		Acrylic Lacquer
Pigment Type		Proprietary
Solvents		Acetone, Toluene, Xylene
MIR		1.40 Max
Fill Weight		11 ounces
Practical Coverage at Recommended DFT (assumes 15% material loss)		Approximately 7 sq.ft./can (0.65 m ² /can)
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	10 minutes
	Handle	1 hour
	Recoat	Anytime
Dry Heat Resistance		200°F (93°C)
Shelf Life		5 years
Flash Point		-156°F (-104°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.