



6439
Speed-Fill™
 Blacktop Filler

SPEED-FILL

- Dries in 60 minutes!
- Fills Cracks Up to 1"
- Seals & Waterproofs
- Our Best Flexible Seal

DESCRIPTION: SPEED-FILL™ BLACKTOP FILLER is a fast drying, rubberized compound for use on the repair of asphalt roads, driveways, pavements, expansion joints and walkways. Speeds up sealcoating jobs with quick drying. Provides a long term flexible repair on cracks and joints up to 1" wide. Also seals foundation walls and other pavement surfaces. Dries to dark black finish.

PREPARATION: Surfaces should be cleaned with spray on cleaner & degreaser and free of any loose materials, grease, oil and dirt, before filling cracks.

EASY APPLICATION: Apply on a clear sunny day when surface temperature is 60 °F and rising. Cut tip to desired opening. Using caulking gun, squeeze material into crack. After material has cured, you may apply a premium driveway sealer or leave by itself. Note: humidity and cool air/surface temperatures may lengthen cure time. Make sure filler has cured before sealing. Do not apply if rain is expected within 12 hours. **DO NOT HEAT.**

CLEAN-UP: Soap and water clean-up immediately after use.

COVERAGE: Provides approx. 32 linear feet of 1/4" bead.

PRECAUTIONS: Protective clothing, gloves and eyewear should be used during application of this product. When transporting this product, ensure that plug is tight and tube secure and upright. Do not allow tube to tumble as this may cause plug to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. For longest life, store in controlled environment, 50 °F - 85 °F. Do not store in direct sunlight. Do not use in drinking water or food systems. Protect from freezing. Seal container when not in use.

WARRANTY AND DISCLAIMER: Gardner-Gibson warrants product to be free of material defects for a period of 12 months, the "Warranty Period", from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper prep and drying conditions must be observed to achieve correct results. Should a product not perform as stated, Gardner-Gibson shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product(s) or refund the purchase price of the defective product. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. **THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GARDNER-GIBSON TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.**

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
6439-9-66	10 fl.oz.	2" x 2" x 11.5"	10 fl.oz. / 296 mL	1.2 lbs.	12/crtn	027134643965

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101