

KOHLER® Roughing-In

K-1139, K-1139-L, K-1139-R
PROFLEX® 6036
BATH WHIRLPOOL

Product Information

Applicable products:	
Bath whirlpool – drop-in	K-1139
Bath whirlpool – tile flange, left drain	K-1139-L
Bath whirlpool – tile flange, right drain	K-1139-R
Fixture*:	
Basin area:	
Bathing well	46" (1168 mm) x 15" (381 mm)
Top area	55" (1397 mm) x 25" (635 mm)
Weight	55 lbs (25 kg)
To overflow	
Water depth	14" (356 mm)
Capacity	57 gal (216 L)
* Approximate measurements for comparison only.	
Drop-in cutout	58-1/2" (1486 mm) x 34-1/2" (876 mm)
Pump:	V Hz A
1-speed	120 60 7.5
Minimum access panel (required):	20" (508 mm) x 15" (381 mm)

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 37 lbs/square foot (181 kg/square meter) loading.

The apron must be installed before the finished floor and wall materials are installed.

This fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-11677)

