

# KOHLER®

## Roughing-In

**K-1146**  
**PROFLEX® 6040**  
**BATH WHIRLPOOL**

### Product Information

Applicable product:			
Bath whirlpool – drop-in			K-1146
Fixture*:			
Bathing well:			
Basin area, bottom	46" (1168 mm) x 19" (483 mm)		
Basin area, top	55" (1397 mm) x 29" (737 mm)		
Weight	56 lbs (25.4 kg)		
To overflow:			
Water depth	14" (356 mm)		
Capacity	54 gal (204.4 L)		
* Approximate measurements for comparison only.			
Pump:	V	Hz	A
1-speed	120	60	7.5
Included components:			
Cut-out template			114859-7

### Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump.	

### Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 30 lbs/square foot (148 kg/square meter) loading.

The suction line extends 1" (25 mm) beyond the edge of the rim. The pump base extends 1-1/8" (29 mm) beyond the edge of the rim. Modify the framing as needed.

A minimum access panel is required as illustrated. This should be 20" (508 mm) wide and 15" (381 mm) high. Locate the access panel at the pump location.

This fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-11677 or K-11677M)

