

KOHLER® Roughing-In

K-1148
PROFLEX® 7242 OVAL
BATH WHIRLPOOL

Product Information

Applicable products:			
Bath whirlpool – drop-in		K-1148	
Fixture*:			
Bathing well:			
Basin area, bottom	53" (1346 mm) x 26" (660 mm)		
Basin area, top	65" (1651 mm) x 34" (864 mm)		
Weight	74-1/4 lbs (33.7 kg)		
To overflow:			
Water depth	15" (381 mm)		
Capacity	78 gal (295.3 L)		
* Approximate measurements for comparison only.			
Pump:	V	Hz	A
1-speed	120	60	7.5
Included components:			
Cut-out template		114861-7	

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 36 lbs/square foot (173 kg/square meter) loading.

This fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements with drain shown. (K-11677 or K-11677-M)

