

KOHLER® Roughing-In

K-1209, K-1209-L, K-1209-R
HOURGLASS® 32
BATH WHIRLPOOL

Product Information

Applicable products:	
Bath whirlpool – drop-in	K-1209
Bath whirlpool – 3-side integral tile flange, left drain	K-1209-L
Bath whirlpool – 3-side integral tile flange, right drain	K-1209-R

Fixture*:	
Basin area	
Basin area bottom	47" (1194 mm) x 20" (508 mm)
Basin area top	53" (1346 mm) x 23" (584 mm)
Weight	100 lbs (45.4 kg)
To overflow	
Water depth	14-1/2" (368 mm)
Capacity	64 gal (242.3 L)
* Approximate measurements for comparison only.	

Drop-in cut-out	58-1/2" (1486 mm) x 30-1/2" (775 mm)
-----------------	--------------------------------------

Pump	V	Hz	A
1-speed	120	60	7.5

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under bath whirlpool must provide for a minimum of 50 lbs/square foot (242 kg/square meter) loading.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

Rim-mount faucet installations: Before drilling the mounting holes, ensure the faucet does not interfere with the drain overflow and circulating system.

Deck-mount spout installations: Consult local and national codes for minimum air gap requirements.

The apron must be installed before the finished floor and wall materials are installed.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

