

### Product Information

Applicable product:	
Fold-up seat on left (shown)	K-12101-*
Fold-up seat on right (not shown)	K-12100-*
* Specify brushed stainless steel grab bars (-C) or polished stainless steel grab bars (-P) when ordering.	
Product is ADA compliant when installed according to the requirements of the Accessibility Guidelines, Section 4.21 Shower Stalls, of the Act.	
<b>ADA</b>	
Recommended accessories:	
Shower drain	K-9132
Dome light	K-1655
Fixture*:	
Configuration	one-piece
Weight	170 lbs (77 kg)
Drain outlet	3-3/8" (8.6 cm) D.
* Approximate measurements for comparison only.	

### Installation Notes

Install this product according to the installation guide.

For optimum accessibility, specify faucets and fittings to install and operate within the control area shown.

For increased accessibility, utilize "pit" installation as detailed in installation guide.

The fixture is not drilled for supply fittings.

Shimming may be required to level the fixture.





Stud opening tolerance + 1/4" (6 mm).

When fire rated construction is specified, dimensions are to the inside of the fire-rated wall.

Some shimming between stud frame and fixture may be required.

Provide clear floor space per ICC/ANSI A117.1 and as shown.

This fixture conforms to ANSI Standard Z124.2. All dimensions are nominal.

*Recess opening must be 45-1/4" (114.9 cm) x 84-1/4" (214 cm).	
	Represents control area for faucets
	Represents 24" (61 cm) wall mount slide bar.
 36" (91.4 cm) 36" (91.4 cm)	Represents clear floor space for 36" (91.4 cm) x 36" (91.4 cm) side entrance.
 48" (121.9 cm) 36" (91.4 cm)	Represents clear floor space for 48" (121.9 cm) x 36" (91.4 cm) front entrance.

