





SHEETROCK® Brand Repair Clips

SHEETROCK Brand Drywall Repair Clips, when used with SHEETROCK® Brand Gypsum Panels, Joint Tape, and Joint Compound, meet building code requirements for repairing one-hour fire-rated drywall partitions. Clips are suitable for both 1/2" and 5/8" thick drywall panels.

Each SHEETROCK Drywall Repair Clips package contains:

- 6 drywall repair clips
 - 12 drywall screws
- Shipping carton contains 6 packages attached to strip hanger.

Instructions

| | | | |
|--|--|---|--|
| <p>1. Cut out damaged panel</p> |  <p>Cut out damaged panel section using a utility knife along the studs and a keyhole saw between the studs. Remove section with hammer and remove old screws or nails.</p> | <p>2. Install SHEETROCK Brand Repair Clips</p> |  <p>Slip drywall repair clips onto the edge of the damaged wall. Position screw about 3/4" from edge and centered between tabs. This will line up screw with the perforations in the clip. Screw through wall into each drywall repair clip.</p> |
| <p>3. Measure and cut new section</p> |  <p>Measure and cut out new drywall panel section to fit damaged area. Screw through new drywall into each drywall repair clip. Screw into drywall; position screw opposite screw holding clip and about 3/4" from edge. Remove tabs from each drywall repair clip.</p> | <p>4. Apply compound and tape</p> |  <p>Apply compound and tape to all four section sides. Do not overlap tape. After first coat has hardened, apply second and third coats of joint compound—allowing each coat to harden before applying next coat—feathering out from previous coats. Sand and prime when dry.</p> |

Trademarks

The following trademarks used herein are owned by United States Gypsum or a related company: SHEETROCK.

Note

Products described here may not be available in all geographic markets. Consult your U.S. Gypsum Company sales office or representative for information.

Notice

We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than their intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from the date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.

