

# KOHLER® Roughing-In

## K-T9492 MASTERSHOWER® RITE-TEMP® PRESSURE-BALANCING VALVE TRIM

### Product Information

Applicable product:	
Pressure balancing valve trim with lever handle	K-T9492-4
Pressure balancing valve trim with round handle	K-T9492-7
Lever handle is ADA compliant. <span style="border: 1px solid black; padding: 2px;">ADA</span>	

Required accessories:	
Rite-Temp® valve <b>OR</b>	K-304-*
HiFlow Rite-Temp valve with stops	K-2971-KS
* For a complete listing of all the Rite-Temp valves, refer to the K-304-* Specification Sheet or Roughing-In Sheet.	

Optional accessories:	
Deep roughing-in kit for K-403-K volume control valve	88013
HiFlow Rite-Temp® Thin Wall Installation Kit	88526
Deep roughing-in kit for Rite-Temp® valve	1007937

### Installation Notes

Install this product according to the installation guide.

**NOTICE: Risk of product damage.** Long screws, for installing trim, can damage the K-2971-KS valve. Consult the trim installation guide to verify if the thin wall installation kit (88526) is needed.

Avoid cross-flow conditions. Do not install shut-off device on either valve outlet.

Cap shower outlet if deck-mount spout, diverter, or handshower is connected to spout outlet.

Install straight pipe or tube drop of 7" (17.8 cm) to 18" (45.7 cm) with single elbow between valve and wall-mount spout.

