

# KOHLER<sup>®</sup>

## Roughing-In

**K-1131, K-1131-F**  
**PROFLEX<sup>®</sup> 7242**  
**BATH WHIRLPOOL**

### Product Information

Applicable product:	
Bath whirlpool – drop-in style rim	K-1131
Bath whirlpool – tile-in flange on three sides for alcove installation	K-1131-F

Fixture*:	
Basin area	
Basin area, bottom	53" (1346 mm) x 26" (660 mm)
Basin area, top	65" (1651 mm) x 34" (864 mm)
Weight	70 lbs (31.8 kg)
To overflow	
Water depth	15" (381 mm)
Capacity	78 gal (295.3 L)
* Approximate measurements for comparison only.	

Drop-in cut-out	70-1/2" (1791 mm) x 40-1/2" (1029 mm)
-----------------	---------------------------------------

Pump:	V	Hz	A
1-speed	120	60	7.5

### Required Electrical Service

Dedicated circuit protected with a Class A Ground-Fault Circuit-Interrupter (GFCI) is required:	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump.	

### Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 36 lbs/square foot (164 kg/square meter) floor loading.

The apron must be installed before the finished floor and wall materials.

This fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

