

### Product Information

Applicable product:			
Custom bath whirlpool – drop-in	K-1131-CE		
Fixture*:			
Basin area:			
Bathing well	53" (1346 mm) x 26" (660 mm)		
Top area	65" (1651 mm) x 34" (864 mm)		
Weight	70 lbs (31.8 kg)		
To overflow:			
Water depth	15" (381 mm)		
Capacity	78 gal (295.3 L)		
* Approximate measurements for comparison only.			
Drop-in cut-out			
	70-1/2" (1791 mm) x 40-1/2" (1029 mm)		
Pump:	V	Hz	A
1-speed	120	60	7.5

### Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump.	

### Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 36 lbs/square foot (174 kg/square meter) loading.

The apron must be installed before the finished floor and wall materials are installed.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

