

Product Information

Applicable product:					
Custom bath whirlpool with heater – drop-in			K-1131-HE		
Fixture*:					
Basin area:					
Bathing well		53" (1346 mm) x 26" (660 mm)			
Top area		65" (1651 mm) x 34" (864 mm)			
Weight		75 lbs (34 kg)			
To overflow:					
Water depth		15" (381 mm)			
Capacity		78 gal (295.3 L)			
* Approximate measurements for comparison only.					
Drop-in cut-out		70-1/2" (1791 mm) x 40-1/2" (1029 mm)			
Pump:		V	Hz	A	
1-speed		120	60	7.5	
Heater:		kW	V	Hz	A
		1.5	120	60	12.5

Required Electrical Service

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Heater	120 V, 15 A, 60 Hz
Locate the outlets behind the whirlpool and within 24" (610 mm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 36 lbs/square foot (176 kg/square meter) loading.

The apron must be installed before the finished floor and wall materials are installed.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

