

Product Information

Applicable product:			
Bath whirlpool, drop-in, custom pump		K-1139-CN	
Recommended accessories:			
Cable drain with PVC tubing		K-7213	
Cable drain without PVC tubing		K-7214	
Trip lever drain		K-11677	
Fixture*:			
Bathing well:			
Basin area	46" (1168 mm) x 15" (381 mm)		
Top area	55" (1397 mm) x 25" (635 mm)		
To overflow:			
Water depth	14" (356 mm)		
Capacity	57 gal (215.8 L)		
Weight	55 lbs (24.9 kg)		
Drop-in cutout	58-1/2" (1486 mm) x 34-1/4" (876 mm)		
* Approximate measurements for comparison only.			
Pump:	V	Hz	A
1-speed	120	60	7.5

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 37 lbs/square foot (181 kg/square meter) loading.

The apron must be installed before the finished floor and wall materials are installed.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

No change in measurements if connected with drain illustrated. (K-11677)

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

