

### Product Information

Applicable product:			
Bath whirlpool	K-712-H2		
Fixture*:			
Bathing well:			
Basin area, bottom	47-1/2" (1207 mm) x 25" (635 mm)		
Basin area, top	55" (1397 mm) x 29" (737 mm)		
Weight	500 lbs (227 kg)		
To overflow:			
Water depth	12-5/8" (321 mm)		
Capacity	64 gal (242.3 L)		
* Approximate measurements for comparison only.			
Pump	kW	V	A*
	1.5	240	11
* Approximate measurements for comparison only.			
Included component:			
Cut-out template	88051-7		

Required accessories:	
Jet trim kit	K-9696

### Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Pump/control	208-240 V, 20 A, 50/60 Hz

### Installation Notes

Install this product according to the installation guide. Floor support under whirlpool must provide for a minimum of 65 lbs/square foot (314 kg/square meter) loading. Cast iron whirlpools are extremely heavy, making some drop-in installations difficult. Splitting the deck/surround is recommended if installing into a deck. Hot water supply should be 70% of capacity or greater. Installations will vary. Fixture conforms to ASME A112.19.1/CSA B45.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7103 or K-7103M)

