

KOHLER® Roughing-In

K-852-HB, K-852-HE TEA-FOR-TWO® 5' BATH WHIRLPOOL

Product Information

Applicable product:	
5' bath whirlpool, custom pump, shown	K-852-HB
5' bath whirlpool, custom pump, top view shown	K-852-HE
ADA compliant when installed per Section 607 of the Act.	ADA

Fixture*:	
Bathing well:	
Basin area, bottom	40-1/2" (1029 mm) x 20" (508 mm)
Basin area, top	52-3/4" (1340 mm) x 24" (610 mm)
Weight	290 lbs (131.5 kg)
To overflow:	
Water depth	13-5/8" (346 mm)
Capacity	60 gal (227.1 L)
* Approximate measurements for comparison only.	

Pump	kW	V	A*
	1.5	240	11
* Approximate measurements for comparison only.			

Drop-in cutout	58-1/2" (1486 mm) x 30-1/2" (775 mm)
----------------	--------------------------------------

Cut-out for undermount	K-586 template
------------------------	----------------

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Pump/control	208-240 V, 20 A, 50/60 Hz
Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 60 lbs/square foot (290 kg/square meter) loading.

Cast iron whirlpools are extremely heavy, making some drop-in installations difficult. Splitting the deck/surround is recommended if installing into a deck.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

Fixture conforms to ASME Standard A112.19.1/CSA B45.2. All dimensions are nominal.

