

Product Information

Applicable products:			
5.5' bath whirlpool, custom pump location	K-856-HE		
5.5' bath whirlpool, custom pump location	K-856-HN		
Fixture*:			
Bathing well:			
Basin area	45" (1143 mm) x 25" (635 mm)		
Top area	58" (1473 mm) x 29" (737 mm)		
Weight	510 lbs (231.3 kg)		
To overflow:			
Water depth	19-1/2" (273 mm)		
Capacity (to overflow)	105 gal (397.5 L)		
* Approximate measurements for comparison only.			
Pump	kW	V	A*
	1.5	240	11
* Approximate measurements for comparison only.			

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Pump/control	208-240 V, 20 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.

Cast iron whirlpools are extremely heavy, making some drop-in installations difficult. Splitting the deck/surround is recommended if installing into a deck.

Floor support under whirlpool must provide for a minimum of 86 lbs/square foot (418 kg/square meter) loading.

A pump/control access panel is required.

For a drop-in installation, the cut-out dimension is 64-1/2" (1638 mm) x 34-1/2" (876 mm).

For an undermount installation, the K-587 template is required.

The hot water supply should be 70% of capacity or greater. Installations will vary.

The pump must be relocated to a custom position at the time of installation. Provide adequate clearance.

Fixture conforms to ASME A112.19.1/CSA B45.2. All dimensions are nominal.

