



**KRUD KUTTER® CONCRETE & DRIVEWAY
PRESSURE WASHER CONCENTRATE**

DESCRIPTION AND USES

Krud Kutter® Concrete & Driveway Pressure Washer Concentrate penetrates and dissolves tough stains on concrete, brick, masonry and asphalt. It contains Oil Grabber®, a unique additive which penetrates the surface to dissolve tough stains from grease, oil, algae, mildew and dirt.

The concentrated formula is ideal for use on concrete, brick, masonry, asphalt, driveways, patios, sidewalks, garage and basement floors. It also prepares surfaces for finishing by promoting the adhesion of paint, stain and sealers.

PRODUCTS

SKU	Description
DG014	1-Gallon Bottle

IMPORTANT – READ ENTIRE LABEL BEFORE USE

- When using a pressure washer to clean painted surfaces, please be aware that water pressure alone may remove paint, or highlight existing discoloration caused by the sun's UV rays.
- From the garden hose, rinse any nearby plants with clean water.
- Always test on an inconspicuous area first.
- Any overspray can be neutralized with large volumes of water.
- In case of severe oil and grease stains on porous surfaces, oil may bleed to the surface or leave a residual stain. Repeat applications may lighten stains, but not remove stains completely.
- Do not mix this product with any other chemicals.

PRODUCT APPLICATION

IMPORTANT: READ ALL INSTRUCTIONS BEFORE APPLICATION

COVERAGE: When mixed 1:10 (12 oz. of concentrate with 1-gallon of water), one bottle of concentrate will make 11 gallons of premix, and clean up to 3,200 sq. ft.

DIRECTIONS: PRESSURE WASHER APPLICATION

Rinse surrounding plants with water, before and after application. Wet the surface to be cleaned, prior to applying the product. Place detergent application siphon tube and screen filter directly into container. Open meter valve (if applicable) for maximum product flow. For reservoir machines, pour product (full strength) into pressure washer. Spray at low pressure onto a wet surface. Allow product to remain on the surface for 5 to 10 minutes to penetrate. Do not allow product to dry on surface. Remove siphon tube from solution and rinse surface with high-pressure spray thoroughly. Flush siphon tube with clean water prior to storage.

DIRECTIONS: HEAVY STAIN REMOVAL

Wet the surface to be cleaned, prior to applying the product. Pour Krud Kutter directly from container on area to be cleaned. Work into surface with a stiff brush or broom. Wait 5 to 10 minutes, then scrub again. Rinse surface thoroughly with water or power wash to remove all cleaner residue.

NOTE: If cleaner dries before rinsing, apply more cleaner, scrub and rinse. When using cleaner on asphalt, some of the natural oils found in asphalt may be removed along with grease and oil. Test a small amount in an inconspicuous area to ensure compatibility. Resealing of asphalt may be necessary after cleaning.

NOTE: For use in a pump up sprayer, mix 12 oz. of concentrate with 1-gallon of water.

NO BLEACH OR AMMONIA. SAFE FOR PEOPLE, PETS AND PLANTS

CAUTION: EYE AND SKIN IRRITANT. In case of contact with eyes or skin, flush with water for at least 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. **Do not induce vomiting.** Get medical attention.

KEEP OUT OF REACH OF CHILDREN.



TECHNICAL DATA

KRUD KUTTER® CONCRETE & DRIVEWAY PRESSURE WASHER CONCENTRATE

PHYSICAL PROPERTIES

		CONCRETE & DRIVEWAY PRESSURE WASHER CONCENTRATE
Composition		Proprietary Ingredients in a Water-based Solution
Weight	Per Gallon	8.7 lbs.
	Per Liter	1.04 kg
Color		Orange Liquid
pH		12-13
VOC (Weight %)		0%
Practical Coverage		1-Gallon – 2,000-3,200 square feet
Shelf Life		NA
Flash Point		>200°F (93°C)
Caution!		CAUTION: EYE AND SKIN IRRITANT. In case of contact with eyes or skin, flush with water for at least 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. Do not induce vomiting. Get medical attention. KEEP OUT OF REACH OF CHILDREN.
Safety Information		For additional information, see MSDS.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.