

Product Information

Applicable products:	
Bath whirlpool with chromatherapy lights	K-1394-H2
Bath whirlpool less chromatherapy lights	K-1394-H3

Fixture*:	
Bathing well:	
Basin area	54-1/2" (1384 mm x 44" (1118 mm)
Top area	61-5/8" (1565 mm) x 54-1/2" (1384 mm)
Weight	260 lbs (118 kg)
To overflow:	
Water depth	19" (483 mm)
Capacity	196 gal (742 L)
* Approximate measurements for comparison only.	

Pump: (Qty. 2)	V	Hz	A
Variable speed:	240	50/60	18

Included components:	
Cut-out template	1006705-7

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Pump/control	220-240 V, 20 A, 50/60 Hz
Heater	220-240 V, 20 A, 50/60 Hz, 4 kW

Installation Notes

NOTE: Pump protrusion beyond rim.

Install this product according to the installation guide.

Two separate 240 V electrical services required; one for the pump/control, and another for the heater.

Floor support under whirlpool must provide for a minimum of 54 lbs/square foot (264 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

