

Product Information

Applicable products:	
Bath whirlpool with chromatherapy lights	K-1397-H2
Bath whirlpool less chromatherapy lights	K-1397-H3

Fixture*:	
Bathing well:	
Basin area, bottom	61" (1549 mm) x 46" (1168 mm)
Basin area, top	68" (1727 mm) x 58" (1473 mm)
Weight	290 lbs (132 kg)
To overflow:	
Water depth	20" (508 mm)
Capacity	215 gal (813.9 L)
* Approximate measurements for comparison only.	

Pump: (Qty. 2)	V	Hz	A
Variable speed:	240	50/60	18

Included components:	
Cut-out template, top (drop-in)	1000554-7
Cut-out template, bottom (drop-in)	1000555-7
Cut-out template, top (flush-mount)	1000556-7
Cut-out template, bottom (flush-mount)	1000557-7

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Pump/control	220-240 V, 20 A, 50/60 Hz
Heater	220-240 V, 20 A, 50/60 Hz, 4 kW

Installation Notes

Install this product according to the installation guide.

Two separate 240 V electrical services required; one for the pump/control, and another for the heater.

Floor support under whirlpool must provide for a minimum of 54 lbs/square foot (264 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck other than that supplied.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

