

KOHLER® Roughing-In

K-1360-H2, K-1360-H3 RIVERBATH® QUADRANGLE WHIRLPOOL

Product Information

Applicable products:	
Quadrangle whirlpool with chromatherapy lights	K-1360-H2
Quadrangle whirlpool less chromatherapy lights	K-1360-H3

Fixture*:	
Bathing well:	
Basin area, bottom	46" (1168 mm) x 34" (864 mm)
Basin area, top	57" (1448 mm) x 37" (940 mm)
Weight	215 lbs (98 kg)
To overflow:	
Water depth	20" (508 mm)
Capacity	149 gal (564 L)
* Approximate measurements for comparison only.	

Pump: (Qty. 2)	V	Hz	A
Variable speed:	240	50/60	18

Included components:	
Cut-out template	1000153-7

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):

Pump/control	220-240 V, 20 A, 50/60 Hz
Heater	220-240 V, 20 A, 50/60 Hz, 4 kW

Installation Notes

Install this product according to the installation guide.

Two separate 240 V electrical services required; one for the pump/control, and another for the heater.

Floor support under whirlpool must provide for a minimum of 62 lbs/square foot (303 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck other than that supplied.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

