

Product Information

Applicable product:	
Bath whirlpool with custom pump and heater – drop-in	K-1160-HD

Fixture*:	
Basin area:	
Bathing well	52" (1321 mm) x 38-3/4" (984 mm)
Top area	61" (1549 mm) x 46-1/4" (1175 mm)
Weight	131 lbs (59.4 kg)
To overflow:	
Water depth	15" (381 mm)
Capacity	96 gal (363.6 L)
* Approximate measurements for comparison only.	

Pump:		V	Hz	A
1-speed		120	60	7.5
Heater:	kW	V	Hz	A
	1.5	120	60	12.5

Minimum access panel (required):	20" (508 mm) W x 15" (381 mm) H
----------------------------------	---------------------------------

Required Electrical Service

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Heater	120 V, 15 A, 60 Hz
Locate the outlets behind the whirlpool and within 24" (610 mm) of the pump and heater.	

Installation Notes

Install this product according to the installation guide.
 Floor support under whirlpool must provide for a minimum of 39 lbs/square foot (189 kg/square meter) loading.
 Fixtures conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

