

Product Information

Applicable product:	
Bowl – elongated	K-4323
Bowl – elongated, with bedpan lugs	K-4323-L
Fixture*:	
Configuration	rear spud, elongated
Water per flush	1.28 gallons (4.85 L)*
Spud size	1-1/2"
Passageway	2-1/8" (54 mm)
Water area	10-1/2" (267 mm) x 9" (229 mm)
Water depth from rim	5-1/4" (133 mm)
Seat post hole centers	5-1/2" (140 mm)
Minimum static pressure required	35 psi (241.3 kPa)
Maximum static pressure	80 psi (551.6 kPa)
Minimum flowing pressure required	25 psi (172.4 kPa)
Required supply minimum	25 gpm (94.6 lpm)
* Designed to flush with 1.28 gallons (4.85 L) of water when installed with a 1.28 gallon (4.85 L) flush valve. Refer to manufacturer and local codes for flush valve requirements.	

Included components:	
Spud	18357
Recommended accessories:	
Stronghold® open-front elongated seat	K-4731-C
Stronghold open-front elongated seat with integrated handle	K-4731-SC
Stronghold Quiet-Close™ open-front elongated seat	K-4731-GC

Installation Notes

Install this product according to the installation guide.

Will comply with the American Disabilities Act (**ADA**) when installed per the requirements of the Accessibility Guidelines, Section 604 Water Closets, of the Act. The Model Plumbing Codes require the installation of elongated open-front toilet seats in public bathrooms.

Will comply with **CSA B651** when installed per Clause 4.3.6 of the standard.

Will comply with **OBC** Barrier Free requirements when installed per Clause 3.8.3.8 and 3.8.3.9.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

