

Product Information

Applicable product:	
Class Five® toilet – left-hand trip lever	K-3575
Class Five toilet – right-hand trip lever	K-3575-RA
Class Five toilet with Insuliner® and tank cover locks – right-hand trip lever	K-3575-RZ
Class Five toilet with tank cover locks – left-hand trip lever	K-3575-T
Class Five toilet with tank cover locks – right-hand trip lever	K-3575-TR
Class Five toilet with Insuliner – left-hand trip lever	K-3575-U
Class Five toilet with Insuliner – right-hand trip lever	K-3575-UR
Class Five toilet with tank cover locks – left-hand trip lever	K-3575-UT

Fixture:	
Configuration	two-piece, elongated
Water per flush	1.28 gpf (4.8 lpf)
Passageway	2-1/8" (54 mm)
Water area	11-1/4" (286 mm) x 8-1/4" (210 mm)
Water depth from rim	5-1/4" (133 mm)
Seat post hole centers	5-1/2" (140 mm)

Included components:	
Bowl	K-4198
Tank	K-4436
Tank cover	84591
Trip lever	K-9380
Tank accessory pack	1016548
Bolt cap accessory pack	1013092

Installation Notes

Install this product according to the installation guide.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

