



## RESIDENTIAL/COMMERCIAL GRADE ASPHALT REPAIR

### PRODUCT DESCRIPTION & USE

Road Rescue® Asphalt Repair is a naturally occurring asphalt material packaged for the purpose of permanently Repairing damaged areas in asphalt surfaces (driveways, parking lots, and roads). By following three simple application steps, Road Rescue® can be applied in hot and cold, wet or dry conditions with no mixing required and is ready for traffic immediately.

### SIZE & YIELD

- 50 lb. (22.7 kg) bags
- Each 50 lb. (22.7 kg) bag when properly compacted and will cover an area of approximately 7 Ft<sup>2</sup> (0.65 m<sup>2</sup>) when placed at a thickness of 1" (25.4 mm).

### APPLICATION

- **Sweep** the area to be filled to remove all loose debris.
- **Fill the hole** with Road Rescue® Asphalt Repair to a height of ½ inch above the surrounding pavement surface.
- Either tamp or drive over Road Rescue® Asphalt Repair to **compact** it into the hole.

Repairs over 1 square foot and 2 inches deep must be applied in 2 inch layers until desired grade is achieved, packing down each layer before applying the next. Once the desired grade is achieved you may immediately open the area to traffic. Allow 30 days to cure before applying a sealer.

If product has become compacted in the bag, you can break it apart by dropping the bag from 12 to 18 inches off the ground. Repeat if necessary. Use a shovel or hand trowel to further break apart compacted material.

### SHELF LIFE

One year provided the bag is not opened resulting in the product being exposed to air. Road Rescue® packaging is UV resistant, allowing the product to be stored outdoors.



### PRECAUTIONS

- Use gloves, safety glasses with side shields, and protective clothing when handling material.
- Avoid inhalation and ingestion.

### WARRANTY

Road Rescue® warrants this product to be merchantable quality when used or applied in accordance with the instruction hereon. This product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is **LIMITED** to the replacement of this product (as purchased) if found to be defective or at the company's prerogative to refund the purchase price. In the event of a claim under this warranty, notice must be given to Road Rescue® in writing at:

Road Rescue®  
200 E. Nopal Suites 202  
Uvalde, TX 78801

\* Refer to [www.roadrescueasphalt.com](http://www.roadrescueasphalt.com) for the most current technical data, MSDS, and guide specifications.

Toll Free: 855.301.1211  
Fax: 830.591.1824  
[info@roadrescueasphalt.com](mailto:info@roadrescueasphalt.com)

200 E. Nopal, Suite 202  
Uvalde, Tx 78801  
Phone: 830: 278.1211