



UNITED COATINGS

ROOF MATE™ SEAM TAPE

PEEL & STICK

DESCRIPTION: United Coatings™ Roof Mate™ Seam Tape is a polyester-reinforced self-adhering tape used in the Roof Mate™ Coating System to repair and reinforce seams in metal and membrane roofs. It bonds to a variety of substrates, including metal as well as aged asphaltic, single ply, concrete, and masonry roofs. Roof Mate™ Seam Tape is easy to use, free of asphalt and solvents, and conforms to local, state, and federal VOC regulations.

APPLICATION: Substrate should be clean and dry before applying Roof Mate™ Seam Tape. Check adhesion to the substrate with a small piece of Roof Mate™ Seam Tape to ensure good bonding. Cut tape to desired length with a knife or scissors. Remove release liner backing and press firmly into place, centering the tape over the crack or seam. Take care to prevent contamination of the adhesive prior to application. Remove any bubbles or buckling by pressing out by hand or utilizing a hand roller. Initial bond is immediate; full bond requires approximately 24 hours. Do not apply at temperatures below 32°F (0°C) or above 110°F (43°C).

See gaf.com for more information.

STORAGE & HANDLING: Store rolls in a cool, dry location and out of direct sunlight.

IMPORTANT: Repair leaks promptly to avoid adverse effects, including mold growth.