

ASSEMBLY AND INSTALLATION INSTRUCTIONS

PD53211 / PD53212 / PD53213 / PD53214

WARNING: BE SURE TO SHUT OFF POWER AT THE MAIN FUSE OR CIRCUIT BREAKER BOX BEFORE INSTALLING OR SERVICING THIS FIXTURE.

**NOTE: 1. Before installing, consult local electrical codes for wiring and grounding requirements.
2. READ AND SAVE THIS INSTRUCTION.**

1. Attach the nipple to the mounting strap, then secure it with a washer and hex nut.
2. Attach the mounting strap to the outlet box by using two mounting screws.
3. Slide the cord clamp then canopy down the free end of the fixture cord so that they both lineup as shown in the diagram.
4. Thread the cord through the nipple and strain relief. Cut the fixture cord to get desired length, making sure to leave 9" extra for wiring.
5. Thread the safety cords up through the holes in canopy by pushing the knobs upward while inserting safety cords.
6. Once the safety cords have been threaded through the knobs and the desired lengths obtained, cut the safety cord at least 3" above the canopy. Tie a safety knot in cords for added security.

Note: The height of the fixture can be adjusted from 10" to 76".

7. Pull out the outlet wires and house grounding wire from the outlet box. Make wire connections using the wire nuts:
 - The smooth wire (marked) from the fixture to the black wire from the power source.
 - The ridged wire (unmarked) from the fixture to the white wire from the power source.
 - The green grounding wire (unmarked) from the fixture to the house grounding wire from the power source.

Carefully put the wires back into the outlet box.

8. Pull the fixture cord down slightly until the Strain Relief touches the hex nut. Attach the canopy up to the mounting strap by inserting the nipple, then secure it with the cord clamp.

Note: Adjusting the strain relief can decrease or increase the length of cord that is exposed.

9. Raise the glass shade and line up the male connectors with holes in glass shade, and secure with female connectors as shown.

Note: Adjust the balance of glass shade by pushing the knobs on canopy and adjusting safety cords.

10. Install bulbs (not included). See relamping label at socket area or packaging for maximum allowed wattage.
11. Turn on the power at the main fuse or circuit breaker box.

