

STRAT-FLEX®

roll-patch

CONTINUOUS PATCH MATERIAL

Designed for repairing multiple drywall applications

roll-patch

APPLICATIONS

- Drywall damage.
- Continuous roll patch allows material to be cut to any length.

PRODUCT DESCRIPTION

- Imprinted with standard electrical outlet patterns to make repairs easy.
- PVC fiber composite material.
- Easily installs using standard drywall compounds.
- Will not fuzz-up during sanding.
- Available in 20' length.



PROFESSIONAL GRADE

roll-patch



roll-patch 5.5

DIRECTIONS FOR USE

- 1 Lightly sand area to be repaired. Trim patch for required use
- 2 Apply drywall compound 1/8"-1/4" thick directly to back of patch.
- 3 Place patch over center of repair and wipe down flat to wall using joint knife. Immediately skim-coat patch and let dry.
- 4 Apply second coat, let dry, and sand. Compound that remains on backside of Roll-Patch makes patch very rigid in the damaged area.

REPAIRS OVER PAINTED SURFACES. Strait-Flex recommends the use of Strait-Flex Super-Bond or latex paint, mixed with all-purpose joint compound, for enhanced bondability.

SPECIFICATIONS ROLL-PATCH 5.5

- 5 1/2" x 20' roll size.
- Color Code YELLOW
- Item# RP-5.5-20S
UPC 6-56690-12564-8
- RETAIL PKG
Case Item# RP-5.5-20R
6 rolls per case.
Case weight: 7 lbs.
24 cases per pallet.

STORAGE

Store in a dry place protected from moisture.