



Do It Yourself Installation Guide

Pebble Top Foam Gym Tile Flooring

Materials Needed:

Utility Knife or Box Cutter

Finished Area - As an Island Layout

For a finished island-like layout, simply interlock the tiles together and easily take off the border strips that are not needed.

Wall to wall installations - Cutting the Material

Use a retractable utility knife or box cutter. Start with a new blade. Change the blade if the tile begins to fray when you are cutting the tile.

Layout Option One - Using some border strips (included).

Step 1. Start by placing one tile in the corner of your room that shares the two longest walls, this corner tile should have two border strips attached, facing the walls.

Step 2. Next, interlock tiles with one border strip attached (along the wall) running away from the corner tile in both directions, covering the floor along the two walls.

Step 3. Interlock all the tiles that do not need to be cut, working toward the opposite corner of the room from where you started. When all the tiles that do not need to be cut are installed, go ahead and start cutting the perimeter tiles to fit up against the wall of your room - leave a 1/4" gap for tile expansion.

For many layouts, you can use one tile in two spaces if the space to fill (against the wall) is less than 10" wide.

Layout Option Two - Using no border strips.

Start the layout in the center of your room. Working outward, interlock the tiles until a full tile will not fit in the remaining perimeter space. Next, begin cutting tiles to fit around the perimeter of your room, leaving a 1/4" gap for expansion. Remember to save the scraps as you may be able to use them to fill another gap in your room.

Please note: When figuring square foot coverage - these tiles will lose 3/8" per tile after interlocking the tiles together.

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
877-822-6622
info@greatmats.com