



IVC US

Residential Installation Guide - Sheet Vinyl

Leading
the Way

IVC US Residential Installation Guide - Sheet Vinyl Flooring

There are three methods of installation suitable for IVC US residential vinyl flooring:

1. Releasable Full Spread Installation Method using Pressure Sensitive Adhesive (Recommended)
2. Loose-Lay Installation (in areas 25 square yards or less and no more than 1 seam)
3. Permanent Full Spread Installation Method (for “special needs” installations)

General Installation Information

The installation method used is dependent upon the day-to-day activities and the overall floor dimensions.

- **The Releasable Full Spread Installation Method** provides optimal performance of the vinyl and is the recommended installation process for all residential IVC fiberglass sheet vinyl products.
- **The Loose-Lay installation Method** should only be used when the flooring area is 25 square yards or less and no more than 1 seam.
- **The Permanent Full Spread Installation Method** can be used for special needs areas, such as those with rolling traffic and/or extremely high traffic. However, **PLEASE NOTE** that if you elect to permanently install your IVC residential flooring using this method as opposed to the recommended Releasable Installation Method that labor rates exceeding residential releasable removal and underlayment will not be covered.

Please contact IVC US Technical Services at **888-225-8287** with any questions.

Releasable Full Spread Installation Method using Pressure Sensitive Adhesive (Recommended)

Materials Required for Installation:

- 3/8” short nap paint roller
- IVC FLEX-TECH Pressure Sensitive Releasable Adhesive
 - If unavailable, approved secondary alternatives include:
 - o Taylor 2037
 - o Henry© 650 R
- **NOTE:** IVC will not be held responsible for problems that may arise for approved secondary alternative adhesives. Please contact the approved secondary alternative adhesives’ manufacturer with issues.
- IVC FLEX-SEAM Premium Seam Bond
 - If unavailable, approved secondary alternatives include:
 - o Taylor 2062
 - **NOTE:** IVC will not be held responsible for problems that may arise for approved secondary alternative seam sealers. Please contact the approved secondary alternative seam sealer’s manufacturer with issues.

This document is reviewed on an ongoing basis. Control # MKF_0012_0 8/13/13

- Duck Acrylic Double Face Tape for Vinyl Floors
- Sharp Utility Knife
- Straight edge
- Push broom
- IVC FLEX -PRIM Acrylic Latex Primer (if priming the floor is necessary)

Acceptable Underlayments

- **Wood underlayment**

Wood underlayment panels must be underlayment grade as specified and warranted by the manufacturer. Always fasten underlayment panels in accordance with the manufacturer's recommendations. Any failure of the underlayment or IVC US flooring as a result of the underlayment is NOT the responsibility of IVC US.

- **Concrete**

- **VCT** (well bonded, on and above grade)
- **Ceramic** (well bonded) with a skim coat
- **Terrazzo** (well bonded)
- **Self-leveling and patching compounds** (latex fortified Portland cement based only)
- **Resilient floor** (no more than 2 layers, well bonded, non-cushioned – residential applications only)
- **Radiant heat floors** (not exceeding 85°F (29°C) and approved by the manufacturer for the use of their product with resilient vinyl flooring applications)
- **Gypcrete** can be utilized when necessary due to radiant heat and in high rise buildings. Gypcrete must be sealed using **IVC FLEX-PRIM Acrylic Latex Primer** to stabilize the surface for adhesive bond. All issues with gypcrete cracking, crumbling, powdering and resulting in the release of adhesive bond are **NOT** warranted by IVC US.

- **OSB (underlayment grade)**

*OSB underlayment panels must be underlayment grade as specified and warranted by the manufacturer. Underlayment panels and joints must be fastened and reinforced according to manufacturer's instructions. Completely sand the floor with a floor sander, so that the floor is smooth and flat. **NOTE:** The chips in OSB overlap. Without sanding properly, OSB has high and low spots throughout the floor that could telegraph through the vinyl.*

- **Surface must be primed using IVC FLEX-PRIM Acrylic Latex Primer.**

- **Particle board (underlayment grade)**

Particle board underlayment panels must be underlayment grade as specified and warranted by the manufacturer.

- **Surface must be primed using IVC FLEX-PRIM Acrylic Latex Primer.**

Floor Preparation

Floor must be clean, smooth, flat and dry. Remove all foreign substances such as wax, grease, dirt, construction markings and contaminants, and any substance or chemical that would interfere with a good bond. Fill all holes and cracks with a latex fortified Portland cement based patching compound. Sand high spots to eliminate the possibility of tele-

graphing. Prime floor if needed with IVC FLEX -PRIM Acrylic Latex Primer to prevent over absorption of adhesives, dust containment, and to ensure a better bond of the adhesive to the subfloor.

Moisture levels at the time of installation of concrete slabs during and after installation must be 5 lbs. or less per 1000 square feet per 24 hours using an anhydrous calcium chloride test according to ASTM F-1869, and pH must be between 5 and 9; or, if using ASTM F-2170 In-Situ Probes should be less than 75% relative humidity.

Inspection of flooring material prior to installation is required. Any defects should be immediately reported to the retail store from which the flooring was purchased before installation. IVC US will not be responsible for labor costs to repair or replace material with defects that were apparent before or noticed at the end of an installation.

The job site and all flooring material and adhesive must be kept for 24 hours before, during and after installation between 65° F and 85° F (18°C and 29°C).

Releasable Installation Method using Pressure Sensitive Adhesive Steps

Step 1

Prepare substrate in order for the surface to be clean, smooth, flat and dry. Under cut all wooden door jambs to maintain a 1/8" relief gap.

Step 2

Place acrylic double face tape at all doorways where a transition strip is needed, next to sliding doors, in front of tubs and shower stalls, and similar areas where an expansion gap will not be covered with trim. Place double face acrylic tape around all floor vents to eliminate air migrating under vinyl causing bubbles. Do not tape along walls or around perimeter of room, as this is not perimeter install flooring.

Step 3

Align the pattern with the most dominant wall to achieve the best appearance in the room. Using a sharp utility knife, trim away excess material along the walls, at cabinets, etc., leaving approximately 2" of vinyl at these areas to be trimmed off later (rough cut).

Step 4

IF A SEAM IS REQUIRED, PLEASE FOLLOW THE "SEAMING INSTRUCTIONS IN A RELEASEABLE FULL SPREAD INSTALLATION METHOD WITH PRESSURE SENSITIVE ADHESIVE."

Step 5

Make relief cuts at corners and projections to allow the material to lay flat before the final cuts are made. Final trimming should be done by cutting in with a utility knife or trimmer leaving a 1/8" to 1/4" expansion gap. The gap allows for sub-floor movement caused by changes in atmospheric conditions. The material should not touch the wall, corners or objects at any point or bubbles or wrinkles may occur. The material must lay flat to stay flat. Final cuts must be made prior to applying adhesive.

This document is reviewed on an ongoing basis. Control # MKF_0012_0 8/13/13

Step 6

Fold back material one half at a time and roll on a consistent layer of IVC FLEX-TECH Pressure Sensitive Adhesive with the 3/8" short nap paint roller.

Step 7

Before placing the material in the adhesive, make sure the adhesive is completely dry (should be dry and tacky to the touch). There should be no transfer of adhesive to material. (If needed, a fan can be used to accelerate drying time.) If the adhesive is not completely dry before installation of material, the adhesive will continue to release gasses causing bubbles under the vinyl material.

Step 8

Position the material in place so that no shifting can occur. Do not lift the vinyl into place because it may shift slightly and wrinkle.

Step 9

Starting in the center of the floor, remove air from under material using a push broom (broom method). **Do not use any type of flooring roller, i.e. 75 or 100 pound.** Do not twist material when placing it onto the adhesive.

Step 10

Repeat steps 6-8 for the remaining portion of the flooring material.

Step 11

Use quarter round or base board to cover the exposed expansion gap. When installing quarter round or any moldings, make sure that they are fastened only to the wall, and do not pinch the material at any point.

** Material not installed in accordance with IVC recommended guidelines, including any and all problems caused by the use of non-recommended adhesive, seam sealer/bond, underlayment and/or improper preparation of the substrate are not covered under the IVC warranty system.*

Seaming Instructions in a Releasable Full Spread Installation Method using Pressure Sensitive Adhesive

1. After adhesive is rolled on and completely dry, position the flooring by over-lapping the seam edges. (Make sure to match patterns)
2. With a straight edge and a sharp utility knife, cut through both layers of flooring material (double-cut) at the designated match point. Make sure the utility knife blade is held in an upright position for a clean 90 degree cut.
3. Remove and discard waste material.
4. Fold back about 8" of the vinyl on one side of the seam and apply a small bead of IVC FLEX-SEAM Premium Seam Bond to one edge of the vinyl that is on the floor.
5. Tuck the seam edges together and wipe off excess bond/sealer with a clean, damp cloth.
6. Use a resilient flooring type hand roller (or wallpaper seam roller) to squeeze out any remaining bond/sealer from the seam. Immediately clean seam with a damp cloth followed by a clean, dry cloth.

This document is reviewed on an ongoing basis. Control # MKF_0012_0 8/13/13

7. Protect the seam and allow it to dry (approximately 6 hours).

Additional Instructions/Notes:

- Always inspect the flooring thoroughly before installation.
- **DO NOT** slide heavy appliances or furniture over or across the flooring. Always lift objects and place them on the flooring or reposition appliances and furniture using hardboards or sliders between the object and flooring while gently repositioning them.
- In-floor heat/AC registers may rest on the vinyl floor, but leave space under registers that are attached to the floor or wall. They should not pinch the flooring material. Be sure to allow a larger opening around the screw to enable movement.
- Apply caulk next to bathtubs, showers, sliding doors or similar areas.
- For bathroom installations, it is not necessary to remove the toilet. Make relief cuts around the perimeter of the toilet and make sure the vinyl flooring is laying flat before trimming off the excess material. Apply caulk around the toilet, next to bathtubs and showers to prevent moisture from getting under the vinyl. Note: if there is a ceramic sanitary cove and no place to install trim mold, you can apply caulk around the walls.
- Make sure furniture legs have large surface, non-staining plastic floor protectors or non-staining felt pads. The protectors should be at least one inch in diameter and rest flat on the floor. The heavier the item, the wider the floor protector should be. Replace small, narrow metal or dome-shaped glides with smooth, flat glides that are in flat contact with the floor.
- Do not use a trowel for application of pressure sensitive adhesive.
- Never use tape around the perimeter of the room.
- Never apply IVC Residential Flooring to wet adhesive. This could cause permanent bond or wrinkling.
- For metal door jambs that cannot be undercut, leave a 1/8" expansion gap and caulk with 100% silicone caulking.

Loose-Lay Installation Instructions

Loose –Lay Installation method is only appropriate for up to 25 square yards and only 1 seam.

NOTE: *Areas with rolling traffic, heavy pivot points, high traffic and stairs/steps/landings are not recommended for Loose-Lay application.*

Materials Required for Installation:

- Duck Acrylic Double Face Tape for Vinyl Flooring
- Sharp Utility Knife
- Straight edge
- Push broom
- IVC FLEX-SEAM Premium Seam Bond (if seaming is required)

- If unavailable, approved secondary alternatives include:
 - o Taylor 2062
 - **NOTE:** IVC will not be held responsible for problems that may arise for approved secondary alternative seam sealers. Please contact the approved secondary alternative seam sealer's manufacturer with issues.
- If a seam is required, you will also need a either a vinyl or wallpaper seam roller

Acceptable Underlayments:

- Hard, flat, clean, sound surfaces, such as wood, concrete, vinyl, etc.).

Floor Preparation:

Floor must be clean, smooth, flat and dry. Remove all foreign substances such as wax, grease, dirt, construction marks and contaminants, and any substance or chemical that would affect the performance of the product.

Inspection of flooring material prior to installation is required. Any defects should be immediately reported to the retail store from which the flooring was purchased before installation. IVC US is not responsible for labor costs to repair or replace material with defects that were apparent before or noticed at the end of an installation.

The job site and all flooring material and adhesive (if adhesive is necessary for certain areas of the Loose-Lay) must be kept for 24 hours before, during and after installation between 65° F and 85° F (18°C and 29°C).

Loose-Lay Installation Instructions:

1. Prepare substrate in order for the surface to be clean, smooth, flat and dry. Under cut all door jambs to maintain a 1/8" relief gap. (If metal jamb, must leave 1/8" expansion gap and caulk before completing job)
2. Align the pattern with the most dominant wall to achieve the best appearance in the room. Using a sharp utility knife, trim away excess material along the walls, at cabinets, etc., leaving approximately 2" of vinyl at these areas to be trimmed off later (rough cut).
3. Place acrylic double face tape at all doorways where a transition strip is needed, next to sliding doors, patio door sills, in front of tubs and shower stalls and similar areas where an expansion gap will not be covered with trim. Place acrylic double face tape around all floor vents to eliminate air migrating under vinyl causing bubbles. Do **NOT** tape along walls or around perimeter of room.
4. Apply an "X" of acrylic double-face tape under appliances and pivot points, making sure not to overlap the tape.
5. Make relief cuts at corners and projections to allow the material to lay flat before the final cuts are made. Final trimming should be done by cutting in with a utility knife or trimmer leaving a 1/8" to 1/4" expansion gap around the perimeter of the room

and cabinets. The gap allows for sub-floor movement caused by changes in atmospheric conditions. The material should not touch the wall, corners or objects at any point or bubbles or wrinkles may occur. The material must lay flat to stay flat.

6. Use the push broom method to thoroughly remove the air from under the vinyl. Make certain all air is removed.
7. Use quarter round or base board to cover the exposed expansion gap. When installing quarter round or any moldings, make sure that they are fastened only to the wall and do not pinch the material at any point.

Seaming in a Loose-Lay Installation:

1. Position the flooring by over-lapping the seam edges. (Make sure to match patterns)
2. With a straight edge and a sharp utility knife, cut through both layers of flooring material (double cut) at the designated match point. Make sure the utility knife blade is held in an upright position for a clean 90 degree cut.
3. Remove and discard waste material.
4. Carefully fold back about 6" - 8" of the vinyl along both edges. Apply a strip of double face tape where the seam edges come together. Press tape firmly to floor. Remove backing from the top of the tape and carefully place back one edge over the tape.
5. While the other edge is still folded back apply a small bead of IVC FLEX-SEAM Premium Seam Bond or an approved alternative seam sealer, Taylor 2062, to the edge of the vinyl that is on the floor.
6. Tuck the seam edges together and wipe off excess bond/sealer with a clean, damp cloth.
7. Use a resilient flooring type hand roller (or wallpaper seam roller) to squeeze out any remaining bond/sealer from the seam. Immediately clean seam with a damp cloth followed by a clean, dry cloth.
8. Protect the seam and allow it to dry (approximately 6 hours).

Additional Instructions/Notes:

- Always inspect the flooring thoroughly before installation.
- **DO NOT** slide heavy appliances or furniture over or across the flooring. Always lift objects and place them on a hard board between the flooring and object and gently reposition them.
- In-floor heat/AC registers may rest on the vinyl floor, but leave space under registers that are attached to the floor or wall. They should not pinch the flooring material. Be sure to allow a larger opening around the screw to enable movement.
- Apply caulk next to bathtubs, showers, sliding doors, patio doors, around metal door jambs or similar areas.
- For bathroom installations, it is not necessary to remove the toilet. Make relief cuts around the perimeter of the toilet and make sure the vinyl flooring is laying flat before trimming off the excess material. Apply caulk around the toilet, next to the bathtubs and showers to prevent moisture from getting under the vinyl. Note: if there is a ceramic sanitary cove and no place to install trim mold, you can apply caulk around the walls.

This document is reviewed on an ongoing basis. Control # MKF_0012_0 8/13/13

- Make sure furniture legs have large surface, non-staining plastic floor protectors or non-staining felt pads. The protectors should be at least one inch in diameter and rest flat on the floor. The heavier the item, the wider the floor protector should be. Replace small, narrow metal or dome-shaped glides with smooth, flat glides that are in flat contact with the floor.
- Never tape around the perimeter of the room.
- Never apply IVC flooring to a wet adhesive (if adhesive is needed for certain areas of the Loose-Lay). This could cause permanent bond or wrinkling and possibly void the warranty.

Permanent Full Spread Installation Method
(for “special needs” residential/property management installations)

The Permanent Full Installation Method can be used for special needs areas, such as those with rolling traffic, extremely high traffic or in areas where cabinets will be installed on flooring or areas with accelerated concrete moisture up to 8 lbs. However, **PLEASE NOTE** that if you elect to permanently install your IVC flooring using this method as opposed to the recommended Releasable Installation Method that labor rates exceeding residential releasable removal and underlayment will not be covered.

Materials Required for Installation:

- 1/16” X 1/32” X 1/32” U notch trowel
- IVC iGrip Permanent Adhesive
 - If unavailable, approved secondary alternatives include:
 - o Taylor 2091 (commercial)
 - o Henry© 650 P
 - **NOTE:** IVC will not be held responsible for problems that may arise for approved secondary alternative adhesives. Please contact the approved secondary alternative adhesives’ manufacturer with issues.
- IVC FLEX-SEAM Premium Seam Bond
 - If unavailable, approved secondary alternatives include:
 - o IVC Infuze Permanent Seal Sealer
- IVC FLEX-PRIM Acrylic Latex Primer
- Duck Acrylic Double Face Tape for Vinyl Floor
- Sharp Utility Knife
- Straight edge
- 100 lb. roller
- Plastic putty knife, 2 clean cloths and appropriate cleaner

Acceptable Underlayments:

- **Wood underlayment**

Wood underlayment must be American Plywood Association (APA) rated underlayment grade as specified and warranted by the manufacturer. All wood subfloors require a

double layer construction. Porous wood underlayments must be primed.

- Any failure of the underlayment or flooring due to the underlayment is **NOT** the responsibility of IVC US. IVC US does not recommend installing resilient flooring over wood flooring or subfloors applied directly over concrete or sleeper-construction floors.

• **Concrete** — See Grade Levels below:

Grade Levels

Suspended: An acceptable suspended floor is a concrete or wood substrate with a minimum of 18” (460mm) of well-ventilated air space beneath it. IVC US recommends that a moisture vapor barrier be placed on the ground below the air space.

On-Grade: An acceptable on-grade floor is a concrete substrate in direct surface contact with the ground at the surrounding ground level. The concrete slab should be protected from moisture penetration and incorporate a proven moisture vapor barrier.

Below-Grade: An acceptable below-grade floor is a concrete substrate partially or completely in contact with the ground below the average surrounding ground level. The concrete slab should be protected from moisture penetration and incorporate a proven moisture vapor barrier.

- **VCT** (well bonded, on and above grade)
- **Ceramic** (well bonded)
- **Terrazzo** (well bonded)
- **Self-leveling and patching compounds** (latex fortified Portland cement based only)
- **Resilient floor** (no more than 2 layers, well bonded, non-cushioned – residential applications only)
- **Radiant heat floors** (not exceeding 85°F (29°C) and approved by the manufacturer for the use of their product with resilient vinyl flooring applications)
- **OSB** (underlayment grade)

OSB underlayment panels must be underlayment grade as specified and warranted by the manufacturer. Underlayment panels and joints must be fastened and reinforced according to manufacturer’s instructions. Completely sand the floor with a floor sander, so that the floor is smooth and flat. Note: The chips in OSB overlap. Without sanding properly, OSB has high and low spots throughout the floor that could telegraph through the vinyl.

- **Surface must be primed using IVC FLEX-PRIM Acrylic Latex Primer.**

• **Particle board** (underlayment grade)

Particle board underlayment panels must be underlayment grade as specified and warranted by the manufacturer.

- **Surface must be primed using IVC FLEX-PRIM Acrylic Latex Primer.**

Unacceptable Surfaces:

- Inter-flex and any perimeter bonded products
- Any floating floor system
- Resilient tile installed below grade
- Carpet
- Cork
- Cushion-back vinyl

This document is reviewed on an ongoing basis. Control # MKF_0012_0 8/13/13

IVC US will not warrant or accept responsibility of any kind for flooring failures related to the use of unacceptable substrates and surfaces.

Floor Preparation:

Floor must be clean, smooth, flat and dry. Remove all foreign substances such as wax, grease, dirt, construction markings and contaminants, and any substance or chemical that would interfere with a good bond. Fill all holes and cracks with a latex fortified Portland cement based patching compound. IVC US only recommends the use of latex fortified Portland cement based products as a satisfactory patching or leveling compound.

IVC US recommends priming extremely porous floors with IVC FLEX -PRIM Acrylic Latex Primer to prevent over absorption of adhesives, dust containment, and to insure a better bond of the adhesive to the subfloor/underlayment.

Moisture Testing: It is the responsibility of the flooring contractor and the installer to confirm all concrete substrates, both old and new, for moisture transmission using the Calcium Chloride Moisture Test according to ASTM F-1869. Moisture vapor transmission should not exceed the recommended levels of 8 lbs. or less per 1,000 sq. ft. in 24 hours. This test should be performed and documented prior to installation. A second testing option determines relative humidity in concrete floor slabs using In-Situ Probes, which should be less than 90% RH per ASTM F-2170 before, during and after installation. These acceptable moisture readings are only applicable when using iGrip adhesive.

PH LEVELS: PH must be between 5 and 9

Inspection of flooring material prior to installation is required. Any defects should be immediately reported to the retail store from which the flooring was purchased before installation. IVC US will not be responsible for labor costs to repair or replace material with defects that were apparent before or noticed at the end of an installation. The job site and all flooring material and adhesive must be kept for 24 hours before, during and after installation between 65° F and 85° F (18°C and 29°C).

PLEASE NOTE: *If removal of existing resilient floor covering is required, follow all recommended Resilient Floor Covering Institute (RFCI) work practices at www.rfci.com.*

Trowel Specifications		
Application Width x Depth x Spacing	Spread Rate	Type of Installation
1/16" x 1/32" 1/32" U Trowel 1.6 mm x 0.8 mm x 0.8 mm U	Up to 350 sq. ft./ gal Up to 8.6 sq. meters / liter	Porous and Non-Porous Substrate

This document is reviewed on an ongoing basis. Control # MKF_0012_0 8/13/13

Permanent Full Spread Installation Steps:

Step 1

Align the pattern with the most dominant wall, and using a sharp utility knife trim away excess material along the walls, cabinet and other permanent objects, leaving approximately 2" of material to be trimmed off later.

Step 2

Make relief cuts at corners to allow the material to lay flat before the final cuts are made. Final trimming does not require a 1/8" to 1/4" expansion gap when using IVC iGrip Permanent Adhesive as this is a permanent installation.

Step 3

Fold back half of the material and apply IVC iGrip Permanent Adhesive to the substrate using the appropriate trowel. If a seam is required, leave an 18" dry zone at the edge of the seam. Then follow the Seaming Instructions in a Permanent Full Spread Installation found below.

Step 4

Do not immediately place the material into wet adhesive. To avoid bubbling, allow time for the adhesive to flash before positioning the material. There will be a slight transfer of adhesive to the skin when it's ready for installation. Do not allow the adhesive to dry completely.

Step 5

Slide the material in place and remove air and vapors under the material using a 100 lb. roller over the entire adhered vinyl.

Step 6

Repeat steps 3-5 for the remaining half of the flooring material.

Seaming Instructions in a Full Spread Permanent Residential Installation:

1. After positioning the flooring, over-lap the seam edges. (Make sure to match patterns)
2. Place a 4"-5" wide scrap of the vinyl between the two layers of vinyl, under the seam area.
3. Double cut through the all layers of vinyl, creating a compression fit when the seam edges are joined.
4. Fold back both sides of the seam area and apply the IVC iGrip Permanent Adhesive to the dry zone. Allow the adhesive to flash before placing the material into the adhesive.
5. Place one side of vinyl into the adhesive and roll the seam using a 100 lb. roller.
6. Apply small bead of IVC FLEX-SEAM Premium Seam Bond or Infuze Seam Sealer along the edge of the installed vinyl.
7. Place the edge of the uninstalled vinyl against the edge of the installed vinyl and press into place.
8. Remove excess bond/sealer using a plastic putty knife followed by wiping the seam area using a clean dry cloth followed immediately with a clean cloth dampened with appropriate cleaner.
9. Using a clean cloth, repeat until all residue is removed from the surface of the vinyl and protect the seam for six hours minimum.

This document is reviewed on an ongoing basis. Control # MKF_0012_0 8/13/13

Additional Instructions/Notes:

- Always inspect the flooring thoroughly before installation.
- **DO NOT** slide heavy appliances or furniture over or across the flooring. Always lift objects and place them on a hard board between the flooring and object and gently reposition them.
- Use caulk next to bathtubs, showers, sliding doors, patio doors, around metal door jambs or similar areas.
- For bathroom installations, it is not necessary to remove the toilet. Make relief cuts around the perimeter of the toilet and make sure the vinyl flooring is laying flat before trimming off the excess material. Apply permanent flexible caulk around the toilet, next to the bathtubs and showers to prevent moisture from getting under the vinyl. **NOTE:** if there is a ceramic sanitary cove and no place to install trim mold, you can apply silicone caulk around the walls.
- Make sure furniture legs have large surface, non-staining plastic floor protectors or non-staining felt pads. The protectors should be at least one inch in diameter and rest flat on the floor. The heavier the item, the wider the floor protector should be. Replace small, narrow metal or dome-shaped glides with smooth, flat glides that are in flat contact with the floor.
- Never tape around the perimeter of the room.

Reversed Installation Guide

If there is a question as to what is considered an allover patter design, please contact IVC US Technical Services at **888-225-8287**.

This document is reviewed on an ongoing basis. Control # MKF_0012_0 8/13/13